

School District of Philadelphia

Office of Capital Programs

440 North Broad Street, 3rd Floor Philadelphia, PA 19130-4015

REQUEST FOR PROPOSALS to provide

PROFESSIONAL ARCHITECTURAL DESIGN SERVICES for BENJAMIN FRANKLIN HIGH SCHOOL – MAJOR RENOVATION

1.0 Subject

The School District of Philadelphia (SDP) is requesting proposals from professional firms for design services for a Major Renovation Project at Benjamin Franklin High School, located at 550 N. Broad Street, Philadelphia, PA 19130.

The School District of Philadelphia was designated a distressed school district on December 21, 2001 pursuant to the Pennsylvania Public School Code ("PSC"), 24 P.S. §6-691(c). The School Reform Commission ("SRC") has been established pursuant to PSC, 24 P.S. §6-696, and is responsible for the operation and management and educational program of the SDP pursuant to PSC, 24 P.S. §6-696(e)(1).

The Office of Capital Programs (OCP) is responsible for identifying and prioritizing capital work within the SDP. OCP shares responsibility for the long term upkeep and replacement of critical building systems over 25.6 million square feet including nearly 500 buildings, annexes, administrative buildings and athletic fields. OCP works closely with the Office of Facilities and Maintenance, the Office of Environmental Management Services, the Office of Real Property, and the Office of General Counsel.

The School Reform Commission adopted the Capital budget for FY 2018 on May 25, 2017. The basis for the budget is the sale of bonds usually repayable with interest over 30 years. The Capital budget is the basis for the multi-year Capital Improvement Program (CIP). Projects are selected for inclusion in the CIP using building condition assessment reports, work order and deferred maintenance data, input from field maintenance employees and school administrators, and the priorities identified in the Superintendent's Strategic Action Plan. CIP priorities include maintaining the physical integrity of existing facilities, upgrading existing facilities to meet code requirements and educational program needs, replacing systems that have exceeded their lifecycle, and constructing new facilities and additions.

2.0 Place and Date of Submission

One (1) original and four (4) copies each of the Technical Proposal and Fee Proposal shall be submitted in separate sealed envelopes clearly marked: "Architectural Services for Franklin Major Renovation – TECHNICAL PROPOSAL - Due 07/31/17" and "Architectural Services for Franklin Major Renovation – FEE PROPOSAL - Due 07/31/17" with the name of the Proposer's firm and their address.

Faxed and Electronically Transmitted Proposals shall not be accepted.

Responses must be received no later than 2:00 pm, Monday, July 31, 2017.

The Proposal shall be addressed to:

The School District of Philadelphia Office of Capital Programs, Suite 371, Office 3165 440 North Broad Street Philadelphia, PA 19130 Attn: Jerry Thompson

3.0 Communications

All questions must be submitted in writing via e-mail to Jerry Thompson, Contracts Manager, gcthompson@philasd.org. The subject line must include the name of the Project: "Proposals for Architectural Services for Benjamin Franklin HS."

The deadline for all questions is 2:00 pm, Monday, July 24, 2017. All responses for every inquiry, including amendments to this RFP, will be provided and posted on the Office of Capital Programs website which can be accessed by clicking on the following link: http://webgui.phila.k12.pa.us/offices/c/capital-program-bids/rfps.

The SDP will not be bound by any oral communications. From the date of the release of the RFP to the date of authorization of a contract, there shall be no communication concerning the RFP between prospective respondents and/or their agents or staff with any SDP staff, except as provided in the RFP. Communication with other SDP staff is expressly prohibited. Any communication in violation of this provision will not be binding on the SDP and shall be grounds for immediate disqualification.

4.0 Mandatory Walkthrough

A mandatory walk through of the project site for Proposers is scheduled for Friday, July 21, 2017 at 2:00 PM at the following location:

Benjamin Franklin High School 550 N. Broad St. Philadelphia, PA 19130

All Proposers shall assemble at the entrance lobby. Each firm is limited to a maximum of four (4) representatives.

5.0 Selection Process Schedule

RFP Issued	7/14/17
Mandatory Walkthrough	7/21/17 @ 2:00 PM
Questions Due	7/24/17 @ 2:00 PM
Proposal Due	7/31/17 @ 2:00 PM
Notification of Finalists	8/3/17
Design Team Presentations	8/4/17, Time TBD
Final Selection of Firm	8/8/17

6.0 Proposal Requirements

<u>6.1 Technical Proposal Requirements</u>

Technical Proposals shall provide the following required information. Organize the proposal to provide section tabs as noted.

Introduction (no tab required)

- o Provide a cover letter explaining the Proposer's understanding of the Scope of Services and a narrative as to why it is qualified to undertake the services described herein. The cover letter shall be signed by an individual authorized to contractually bind the proposal.
- Provide a Table of Contents.

<u>Tab 1 – Project Experience</u>

- o Describe completed projects (5 maximum) of comparable type, scope and complexity. Include a project summary, design period, year completed, construction budget, and construction cost. Include photographs, renderings and drawings as necessary to describe project scope and design innovations applied. Highlight projects on which the proposed firm and consultants have worked together successfully.
- o Describe the Proposer's experience leading student and community design charrettes and incorporating outcomes into project design.
- Describe the Proposer's experience coordinating phased projects in occupied existing buildings.
- Describe the Proposer's experience with projects in which the scope of work included co-location of two or more school programs.
- Describe the Proposer's familiarity and experience with the permitting process in the City of Philadelphia.
- o Describe the proposed team's history of successfully, and seamlessly, working together on projects of comparable type, scope and complexity. Describe the Proposer's procedures, including QA/QC, for producing coordinated drawings between the Proposer's firm and its consultants.
- o Describe the Proposer's experience and ability to design a project with strict adherence to the proposed scope and budget. Describe the Proposer's firm's approach to, and experience with, performing value engineering.
- o Describe the Proposer's experience with, and process to, minimize change orders and change order costs during construction.
- Describe the Proposer's experience and ability to meet or reduce proposed schedules; any techniques that have been used to reduce proposed schedules should be explained in detail. Describe the Proposer's method to assist in construction administration to meet the construction completion dates.

<u>Tab 2 – Project Organization and Personnel Qualifications</u>

- o Provide an organizational chart of the team being proposed including all personnel and consultants. The chart should describe the organizational structure indicating how the team will be managed and who holds key decision-making ability. The chart should include all individuals involved at any point in the project and indicate those roles that will not be required for the entire duration of the project.
- o Provide resumes of all key personnel that will perform the required services. Include experience on similar projects, professional certifications, and technical expertise. Key personnel include but are not limited to: Principal, Project Manager, Project Architect, Construction Administrator, Interior Designer, Educational Planner, Landscape Architect, Civil Engineer, Mechanical Engineer, Plumbing Engineer, Structural Engineer, Fire Protection Engineer, Specification Writer, and Cost Estimator.
- Provide two references for each key team member including current telephone numbers for persons with whom they have had professional dealings within the last three years.
- o Provide copies of certificates proving professional registration in the State of Pennsylvania of all staff and consultants who will sign and stamp the contract documents.

Tab 3 - Project Approach

- Provide a narrative describing the Proposer's approach to the project including the following:
 - o Indicate a clear understanding of project goals and objectives;
 - o Describe approach for verifying the scope of work;
 - Highlight elements of the scope of work that stand out as opportunities for design innovation and / or potential obstacles to project success;
 - Describe how specialized expertise of key personnel will be deployed on the project;
 - o Describe initial design concepts;
 - o Describe approach to phasing;
 - Describe in detail techniques that will be used to meet or reduce the schedule defined in the scope of work including a bar chart;
 - Describe in detail techniques that will be used to meet or reduce the budget defined in the scope of work.

Tab 4 - Project Schedule and Plan

Utilize the milestones provided below to provide a summary-level Critical Path Method schedule from design through construction administration and project close-out. Integrate critical design activities and building and zoning permit applications. Illustrate an understanding of SDP processes, required project approvals, and duration for design reviews.

SRC Resolution	8/17/17
Design NTP	8/18/17
Schematic Design	8/18/17 – 10/13/17
Design Development	10/14/17 – 1/5/18
Construction Documents	1/6/18 – 3/16/18
Bid Documents	3/17/18 – 4/27/18
Advertisement	5/18/18
Bid Date	6/19/18
SRC Resolution	June 2018
Construction	July 2018 – July 2019

<u>Tab 5 - Proof of Current Insurance Coverages</u>

Provide Certificate(s) of Insurance reflecting current insurance coverage of the Proposer's firm for the following:

- 1. Workers' Compensation and Employers' Liability Insurance
- 2. Commercial General Liability Insurance
- 3. Automobile Liability Insurance
- 4. Professional Liability Insurance
- 5. Excess Umbrella Insurance

Successful Proposer(s) must provide evidence of current insurance coverage prior to execution of the contract. The amounts and types of such insurance coverages are indicated in the Professional Design Services Contract (see Attachment A).

<u>Tab 6 – Good Standing or Subsistence Certificate</u>

All Proposers must submit a copy of their firm's Good Standing or Subsistence Certificate issued by the Pennsylvania Department of State, Corporation Bureau. Certificates may be ordered online or by calling (717) 787-1057. Proposers may have to register their companies before ordering.

<u>Tab 7 - Completed Executed Forms & Attachments</u>

Proposers shall complete the attachments as follows:

- o Architect-Engineer Qualifications Form
 - The Proposer must submit a completed SF 330 Architect-Engineer Qualifications form. Standard Form 330 and related instructions can be downloaded here:
 - https://www.gsa.gov/portal/forms/download/116486.
- o Agreement to Contract Terms and Conditions See Attachment A
 The Proposer shall review the sample contract listed below this RFP on the
 solicitation website and complete the form acknowledging that they are
 in agreement with SDP's Professional Services Contract and no changes
 will be made to the Contract.
- o City of Philadelphia Tax Compliance
 - Provide a copy of the Proposer's "Certificate of Tax Clearance" with the City of Philadelphia. Search for the firm's tax compliance status at this link: https://secure.phila.gov/revenue/TaxCompliance. If the firm is compliant, print and attach the certificate. If the firm is not compliant, please contact the City Revenue Department Tax Clearance Unit at (215) 686-6565.
- Anti-Discrimination Policy & Equal Opportunity Non-Discrimination Notice
 See Attachment B
 - The Proposer must sign the form acknowledging and agreeing to adhere to the District's Anti-Discrimination Policy.
- M/WBE Participation Plan Form See Attachment C
 The Proposer must complete the M/WBE Participation Plan form below.

 Respondent to this RFP will include 15%-20% sub-consultant participation with either a minority-owned business enterprise(s) and/or with a woman-owned business enterprise(s).

Tab 8 - Acknowledgment of Receipt of Addenda (if any)

The Proposer will acknowledge and list the number of addenda received.

<u>Tab 9 - Company's Financial Statements</u>

The Proposer must submit the firm's most recent audited financial statement, which shall include, at a minimum, a balance sheet, related statements of income and retained earnings and cash flows and footnotes.

6.2 Fee Proposal Requirements - See Attachment D

The method of compensation shall be based on the Percentage of Construction Cost Method. The final fee shall be adjusted based on the actual low construction bid amount. Hourly rates will be utilized for additional services. The Proposer shall complete all pages of the fee proposal.

7.0 Budget

The current estimated construction budget is \$20,000,000.

The Project Budget has been established based on preliminary planning and cost estimates performed by the SDP Office of Capital Programs. It is the obligation of the selected firm to design the Project within the budget restrictions established for the Project.

8.0 Project Intent & Scope of Work

Goals

This major renovation project includes upgrades to building systems and components as well as the co-location of two high school programs, each with a population of 500 students.

The goals of the School District of Philadelphia in performing this work are as follows:

- Co-locate two high school programs in an equitable manner: provide a distinct point of entry and identity for each of the two programs while optimizing opportunities for collaboration including improving communication and maximizing common spaces;
- Provide interior upgrades that foster collaborative, student-centered learning environments:
- Replace or improve critical building systems that have exceeded their life expectancy and provide alternate approaches where possible.

Background

Benjamin Franklin High School is located just North of Center City. The property is bounded by Green Street to the North, Brandywine Street to the South, Broad Street to the East and North 15th Street to the West. The school's entrance faces Broad Street. There is no parking on site. The facility is 242,293 sf.

The original 1958 building is six stories with a full basement. A one story addition with a basement was added in 1971; the addition contains the auditorium, gym, and supporting spaces. Portions of the basement are in the process of a complete renovation to accommodate vocational training classrooms.

The original building structure consists of reinforced concrete (basement) and structural steel framing (upper floors) with stone clad masonry at East and West ends and curtain wall infill at North and South. The curtain wall contains double hung window inserts and granite spandrel panels. The addition is primarily face brick on CMU backup with steel trusses and precast panels at the roof. The envelope also includes stainless steel-framed storefront with aluminum framed window inserts and stainless steel glazed doors at the entrance and auditorium lobby and hollow metal egress doors elsewhere. The roof is a built-up system installed approximately twenty years ago.

Interior building partitions are typically painted CMU and glazed CMU. Interior doors are typically solid core wood, some glazed, with hollow metal frames. Ceilings are typically exposed and painted with some areas of suspended or surface-mounted acoustic tiles.

Flooring is typically VAT with some areas of carpet and terrazzo. Stairs are concrete with cast iron, non-slip treads.

Scope of Work

The following list is provided as a guide of anticipated scope items. The successful Proposer shall be fully responsible to verify existing conditions in the field and confirm scope of work. Work will be phased such that school program will remain in operation through construction. Please see Appendix A: Site Assessment Report for detailed descriptions of deficiencies.

BUILDING ENVELOPE / EXTERIOR

- o Remove existing roofing assembly down to the top of the existing structural slab and provide new 3-ply SBS-modified bitumen and insulation. Remove existing coping and provide new metal coping around entire building perimeter. Remove and replace existing roof drains down to the first joint.
- o Replace curtain wall frame and panels on original building. Provide hopper windows with 1" insulated glazing and insect screens. Provide integral security screens at first floor.
- Repair façade as follows: Patch concrete at areas of spalling, clean and coat steel and patch concrete at areas of exposed rusting reinforcement (these conditions observed primarily at fifth floor open play area,) repair cracks and repoint masonry joints where required.
- o Replace all exterior hollow metal service and egress doors and frames.
- o Provide separate entries for each of the two co-located school programs identified by exterior signage.
- o Renovate existing rooftop recreation area at west end of 6th floor to provide a clean, safe and functional recreation space.

INTERIOR

- o Interior upgrades do not apply to Basement as program spaces on this floor were recently renovated.
- o Provide accessible entry at the 15th Street entrance.
- Provide accessible hardware at interior doors.
- Replace bathroom partitions and accessories and provide accessible stalls.
- o Replace acoustic tile ceilings (about 15% of ceilings).
- o Replace VAT floors (approximately 80% of floors) with new vinyl flooring.
- Replace carpet flooring.
- o Paint selective accent walls at classrooms and corridors.
- o Paint corridor lockers with electro-static paint.
- o Refurbish existing elevator cabs.
- Demolish interior non-bearing CMU partition walls / provide new metal stud and GWB partition walls to accommodate new room layouts at reconfigured spaces.
- o Provide new panic hardware at egress doors.
- Provide additional ADA upgrades as required per Philadelphia Building Code (2009 International Existing Building Code).

EDUCATIONAL

- o Educational upgrades do not apply to Basement as program spaces on this floor were recently renovated.
- o Upgrade one IMC to be used by both co-located programs.
- o Provide or upgrade approximately four Career and Technical Programs.
- o Provide casework and sink in approximately two new art rooms.

- o Provide science room equipment for approximately six (four wet and two dry) new science labs including fume hoods, teacher's demonstration tables, casework, student lab tables with sink and power, and emergency eye wash stations. Provide casework with sinks at prep rooms.
- o Remove existing display surfaces (tack/white/chalkboards) and replace at all classrooms in type / quantity consistent with SDP standards for classroom modernization.

FLECTRICAL / IT

- o Provide new panelboards.
- o Replace lights at classrooms and offices (primarily T12) with LED fixtures.
- o Replace all exterior light fixtures with LED fixtures.
- o Replace all exit signs with LED exit signs.
- Provide two wireless central clock / public address systems to serve each school program separately.
- o Provide independent audio/visual intercom system at main entrances and loading dock with central controls to serve each school program separately.
- o Provide upgraded infrastructure for power and data consistent with SDP standards for the Ideal Technology Scenario for all classrooms. Provide additional power and data infrastructure to support 1-to-1 computing including at auxiliary spaces as required by SDP IT. Power and data ports should be re-used to the maximum extent that is technically feasible. Scope should be applied consistently throughout the facility, across two co-located programs.

MECHANICAL

- o Replace water distribution piping.
- o Replace unit ventilators and fin tube radiators throughout.
- o Provide new AHU to serve cafeteria and kitchen.
- Replace select AHUs including providing new unit to serve cafeteria and kitchen.
- o Replace split system serving LAN room.
- o Replace exhaust fans.

ENVIRONMENTAL

o The SDP Office of Environmental Management & Services (OEMS) will develop scope of work for remediation services where applicable. Work will involve the removal of mold- and asbestos- containing materials prior to any investigation or repair can occur as well as abatement associated with the scope described above.

9.0 Phases of Service

The following list provides an overview of deliverables. Phases of services and deliverables shall comply with the requirements described and detailed in the Sample Contract as noted in Attachment A. Documents shall be coordinated for bidding under separate contracts per Public School Code.

- Survey of existing facility including electrical, IT, mechanical and plumbing infrastructure to confirm scope of work;
- Program confirmation of both high school programs followed by a design / planning charrette with SDP administrators, students and staff across both programs;
- Presentation of three space plan options for collocation;

- Design Development (60%) submission documenting selection and sizing of all building and construction components, finish board and renderings, and updated specifications and detailed construction cost estimate*;
- Construction Documentation (90%) submission providing all project details with final specifications, phasing plan and detailed construction cost estimate;
- Bid Documentation (100%) submission providing a completed set that can be used for regulatory approvals, bidding and construction;
- Meeting documentation and dissemination of minutes for all design meetings after kick-off;
- Budget reconciliation at all phases of design;
- Value Engineering services;
- Participation and presentation at community meetings;
- Preparation and submission of all required permit applications including full participation during all city, state and federal government agency reviews and prerequisite approvals;**
- Bidding and Construction Administration including meeting documentation and dissemination of minutes for all construction meetings;
- Participation in all closeout activities including commissioning and start-up of major building systems and equipment;
- Participation in one-year post construction and warranty reviews.

Reimbursable Services:

 Retain a licensed electrician to survey existing panels, circuitry and breakers to confirm circuitry routing for terminal equipment and remaining capacity of panel boards to serve new and upgraded equipment.

* All cost estimates at all phases shall be in CSI Masterformat. Please see Appendix B for cost estimate cover sheet to accompany each detailed cost estimate.

* *Except as specifically indicated otherwise, the selected firm shall be responsible for all research, documentation and filing for approvals required of regulatory agencies for the Project. The design developed by the selected firm and its consultants shall be in compliance with all required codes and regulations, and the design documents shall clearly indicate the code requirements that affect the design and the method in which the design complies with the code and regulatory requirements. When code and regulatory requirements are vague, are subject to interpretation or conflict with other code and regulatory requirements, the selected firm shall be responsible for obtaining and documenting interpretations and decisions from the proper regulatory agencies in a timely manner so that the interpretations and decisions will not adversely affect the progress of the design.

A number of approvals may require presentations made to public commissions, and the selected firm shall properly prepare for such presentations including practice sessions of the presentation made to SDP representatives.

The selected firm shall schedule consultations and meetings with regulatory agencies as soon as possible in the design process. Required changes to designs that result from reviews by these agencies shall not be considered as grounds for extension of time to the Project Schedule or modification to the selected firm's compensation for the design.

The following are typical regulatory agency approvals required for SDP projects (This list does not necessarily include all required approvals):

City of Philadelphia Water Department

- City of Philadelphia Streets Department
- City of Philadelphia Art Commission
- City of Philadelphia Historic Commission
- City of Philadelphia Planning Commission
- City of Philadelphia Zoning Commission
- City of Philadelphia Health Department
- City of Philadelphia Department of Licenses and Inspection
- City of Philadelphia Fire Department
- Philadelphia Parks and Recreation
- NPDES through the Pennsylvania Department of Environmental Protection
- Utility Companies such as PECO and Philadelphia Gas Works (PGW)

In addition, the School District of Philadelphia coordinates PlanCon approvals through the Pennsylvania Department of Education. The selected firm shall work with and furnish data and information to the SDP and attend review meetings at the Department of Education related to this process.

10.0 Selection Procedure & Evaluation Criteria

A responsive proposal is complete and addresses all requirements of the RFP. Each proposal will be reviewed by the SDP selection committee to determine responsiveness. Proposals deemed non-responsive will be rejected without evaluation. The SDP reserves the right to reject any or all proposals when such rejection is in the best interest of the SDP. The SDP reserves the right to waive any informalities and technicalities in the RFP process or any non-material defects in proposals. The SDP may at any time terminate the RFP process provided for herein for any reason or no reason at the sole discretion of the SDP. The receipt of proposals or other documents by proposers during any state of the RFP process shall in no way obligate the SDP to enter into any agreement with any proposer or make the SDP liable for any proposer costs. The SDP may alter these and any other procedures as it deems necessary and appropriate.

If for any reason whatsoever the SDP rejects any proposer's proposal, the proposer agrees that it will not seek to recover lost profits on work not performed nor will it seek to recover its proposal preparation costs. By submitting its proposal, the proposer expressly states that it intends to be legally bound and accepts the limitation of remedies set forth in this paragraph. By submitting its proposal, the proposer further expressly states that should it file, initiate, or persuade another to file, initiate or in any other manner pursue or encourage any lawsuit or that such filing, initiating, or other pursuit constitutes a breach of its agreement with the SDP and that it will be liable for damages incurred by the SDP arising from the breach of this agreement including, but not limited to, the SDP's attorneys' fees and costs of defending such action.

Selection - Stage 1:

Proposals shall be evaluated by a selection committee. Each member of the selection committee will assign a score to the proposal based on the following evaluation criteria:

- A. Technical competence and qualifications of the Proposer's firm as evidenced by professional experience in the satisfactory performance of design services for projects of comparable size, building type and complexity;
- B. Technical competence and qualifications of the assigned personnel as evidenced by the education and experience of key team members in providing the services described herein;
- C. Project approach including preliminary design ideas, schedule control and budget control;

- D. The quality of references from past or current clients, preferably regarding projects of comparable type, size, and complexity to the projects described herein;
- E. History of Proposer in successfully meeting schedules and budgets with special consideration for minimizing change orders and coordinating phased construction in occupied buildings;
- F. Meeting of M/WBE goals required in Attachment C.

Each Proposer's firm will receive a ranking based on the selection committee's scores. A limited number of firms (to be determined by the SDP) with the highest rated technical proposals will be selected as finalists and invited to make a presentation to the selection committee. Proposers must be prepared to make a presentation on the date noted in Section 5.0. Project managers and key personnel are expected to attend the presentations. The finalists shall be prepared to present and respond to questions on preliminary design solutions, approach to major architectural and building systems, unique qualifications of the Proposer's firm, cohesiveness of proposed team, and approach to schedule and budget control. The selection committee will once again evaluate each firm using a pre-established scoring rubric.

Selection - Stage 2:

The fee proposal of the highest rated firm will be opened and the SDP will enter into fee negotiations. (Fee proposals for the other firms will not be opened until such time as the firm in question has been selected for fee negotiation.)

If the SDP cannot reach an agreement on fee with that firm, negotiations with that firm shall be terminated. The fee proposal of the next highest rated firm will be opened and fee negotiations with that firm commenced.

The process will be repeated as necessary until agreement is reached or the SDP elects to terminate this solicitation.

Notification of Award

Selected Prime Proposer(s) shall be approved by the School Reform Commission, after which the SDP will notify the successful Prime Proposer(s) of the award and prepare and distribute the necessary documents for execution. The unsuccessful Prime Proposers will be notified by letter after the awarding of the contract.

ATTACHMENT A

SAMPLE PROFESSIONAL DESIGN SERVICES CONTRACT

The "Professional Design Services Contract" shall serve as a "sample" document for the Proposer(s) to review. Said "sample" contract shall not be construed as a contract between the Prime Proposer and the SDP. The Sample Contract can be viewed by first clicking on the link below, then clicking on the link to the RFP for this project at the top of the page. The Sample Contract will be listed in a table immediately below this RFP.

Link to SDP Office of Capital Programs Request for Proposals Page

I have read the sample "Professional Design Services Contract" and agree to enter into a Contract for this Project under the Terms and Conditions of the Contract and will not take any exceptions to the Terms and Conditions.

Proposer's Firm Na	me:	
Corporate Seal:	Affix Here	
Signature:		(Principal / Owner)
Title:		
Date:		

ATTACHMENT B ANTI-DISCRIMINATION POLICY of the SCHOOL DISTRICT OF PHILADELPHIA ADOPTED NOVEMBER 14, 2007

SECTION 1. THE POLICY

It is the policy of the School District of Philadelphia (the "District") acting through and by the School Reform Commission (the "SRC") to ensure equal opportunity in all contracts let by the District (the "Contracts"). In light of this policy, the District has adopted this Anti-discrimination Policy (the "Policy") which is applicable to all Contracts, including but not limited to, Contracts for the design, development, construction, operation and maintenance of school buildings and other buildings and structures owned, leased or used by the District or its contractors, assignees, lessees and licensees (the "Facilities"); Contracts for professional services and Contracts for the purchase of goods, services, supplies and equipment for the District and the Facilities. The objective of the Policy is the promotion of prime contract and subcontract opportunities for minority and woman-owned business enterprises ("M/W/BEs") that are approved by the District or that are certified by the Minority Business Enterprise Council of the City of Philadelphia, Southeastern Pennsylvania Transportation Authority or any other certifying agency designated by the District in its discretion.

The fundamental requirement of the Policy is that all contractors, vendors and consultants that contract with the District (the "Contractors"), satisfy the District that they will: (1) not discriminate against any person in regard to race, color, religion, age, national origin, sex, ancestry, handicap or disability; and (ii) provide a full and fair opportunity for the participation of M/W/BEs in Contracts. Contractors must demonstrate that the participation of M/W/BEs is "meaningful and substantial" in all phases of a Contract under criteria adopted by the District. "Meaningful and substantial" shall be interpreted by the District as meaning the range of participation that reflects the availability of bona fide M/W/BEs in the Philadelphia Metropolitan Statistical Area. Participation shall be measured in terms of the actual dollars received by M/W/BEs.

As used in this Policy, the word "Contractors" includes any person, firm, partnership, non-profit corporation, for-profit corporation, Limited Liability Company or other legal entity that contracts with the District.

For purposes of this policy, "minority person" refers to the following: African American or Black (persons having origins in any of the Black racial groups of Africa); Hispanic American (persons of Mexican, Puerto Rican, Cuban, Dominican, Central or South American, or other Spanish or Portuguese culture or origin regardless of race); Asian American (persons having origins from Japan, China, Taiwan, Korea, Burma (Myanmar), Vietnam, Laos, Cambodia (Kampuchea), Thailand, Malaysia, Indonesia, the Philippines, Brunei, Samoa, Guam, the U.S. Trust Territories of the Pacific Islands (Republic of Palau), the Commonwealth of the Northern Marianas Islands, Macao, Fiji, Tonga, Kiribati, Juvalu, Nauru, Federated States of Micronesia, Hong Kong, India, Pakistan, Bangladesh, Bhutan, the Maldives Islands, Nepal or Sri Lanka); and Native Americans (which includes persons who are American Indians, Eskimos, Aleuts or Native Hawaiians).

SECTION 2. PROCEDURES FOR IMPLEMENTATION

1. Articulation of the Policy. Staffing and Reporting

The Office of General Counsel and Office of Small Business Development will develop language to be included in bid solicitations and requests for proposals that clearly sets forth the objective of the Policy (the "Solicitation Language"). District employees shall include the Solicitation Language in all bids, public solicitations, requests for proposals and all communications to potential Contractors, including those who wish to provide professional services to the District. The Policy shall be articulated to the public in general, and to each Contractor, assignee, lessee or licensee doing or seeking to do business with the District. The District may employ additional staff or contract with other public or private entities to assist in the implementation of the Policy. SBD shall provide the SRC with annual reports on the level of M/W/BE participation in all contracting activities.

2. Promotion of M/W/BEs

The District recognizes the importance of having meaningful and substantial M/W/BE participation in all Contracts. To that end, the District will take steps to ensure that M/W/BEs are afforded a fair and equal opportunity to participate. Those steps may include but are not limited to: (i) making public contracting opportunities; (ii) advertising in newspapers and periodicals published by community-based organizations and M/W/BEs; and (iii) designing bid packages in such a way as to promote rather than discourage M/W/BE participation.

3. Contracting Requirements

a. Bids, Request for Proposals, and Public Solicitations

Prior to the dissemination of any bid, request for proposals or public solicitation (the "Solicitation"), the applicable contracting department of the District shall submit proposed ranges of M/W/BE participation in the area to be bid (the "Participation Range") to SBD for approval. The Participation Range, as approved by SBD, shall be included in each Solicitation and, if applicable, the Solicitation shall include the names and addresses of bona fide M/W/BEs that are available for contracting or joint-venture opportunities. Each bidder or respondent shall be required to submit: (i) a plan with its bid or proposal that meets the Participation Range set forth in the Solicitation and lists the names, addresses, dollar amounts and scope of work to be performed by M/W/BEs (the "Participation Plan"); or (ii) brief narrative explaining its reasons for not submitting a Plan that meets the Participation Range set forth in the Solicitation.

Submission of the Participation Plan is an element of responsiveness. Failure to submit a completed Participation Plan or a narrative explaining the reasons that the Participation Ranges could not be met may result in the rejection of a bid or proposal. If the Participation Range in a bid or proposal meets or exceeds the level determined by the District to be meaningful and substantial, there shall be a presumption of compliance with the Policy. If, however, the proposed Participation Range falls below the level determined by the District to be meaningful and substantial, the bidder or respondent must prove to the satisfaction of the District that it did not discriminate in the solicitation of potential subcontractors and/or joint venture partners.

b. Contracts for Professional Services

Contracts for professional services that are not the subject of a Solicitation must also include approval Participation Plans. If a proposed Contract for professional services is subject to the approval of the Limited Contracts Authority Committee of the District (the "LCA"), the applicable contracting department shall submit a proposed Participation Plan for the written approval of SBD prior to the submission of the Contract to the LCA. In instances where proposed Contract for professional services must be approved by a Resolution adopted by the SRC, SBD's approval of the Participation Plan shall be incorporated into the on-line resolution process prior to the submission of Resolution to the SRC.

4. Sanctions

The Participation Plan shall be a part of each Contract between the District and a Contractor and shall be enforceable as any other contractual term or condition. Sanctions for breach of a Participation Plan may include suspension, cancellation of the Contract and/or disbarment from future contracting opportunities with the District.

EQUAL OPPORTUNITY

A. EQUAL OPPORTUNITY

The School District of Philadelphia (the "School District") is an Equal Opportunity Employer and demands no less of the companies with which it does business. The School District will not do business with companies or persons who unlawfully discriminate on the basis of race, color, national origin, sex, creed, disability, or any other impermissible ground in their hiring, promotion, subcontracting or procurement practices. By submitting any proposal to contract or entering into any contract with the School District, the Respondent (the "Respondent") represents and certifies that Respondent is an Equal Opportunity Employer; and conducts business affairs without improper regard to race, color, national origin, sex, creed, or disability, and has not been debarred, suspended, or declared ineligible to contract by any

public or private agency or entity because of the Respondent's discriminatory practices. If the Respondent has been debarred or suspended, Respondent must submit a statement with the bid identifying the debarring or suspending entity and giving the date that the debarment or suspension was or is scheduled to be lifted. All certifications contained in a Respondent's proposal are material representations of fact upon which reliance will be placed if the School District awards a contract pursuant to this Request for Proposals. If it is later discovered or determined that the Respondent knowingly rendered an erroneous certification, then the School District may pursue available remedies, including termination of the contract.

B. NON-DISCRIMINATION

1. Non-Discrimination in Hiring

The Respondent agrees that it will comply with provisions of the Philadelphia Fair Practices Ordinance administered by the Human Relations Commission of the City of Philadelphia, the Pennsylvania Human Relations Act. No. 222, October 27, 1955, as amended, 43 P.S. Section 951 et seq; Title 7 of the Civil Rights Act of 1964, 42 U.S.C. Section 2000 et seq., and all pertinent regulations adopted pursuant to the foregoing in providing equal employment opportunities in connection with all work performed by it pursuant to any contract awarded to Respondent, (the "Contract"). The Respondent therefore agrees:

- (a) That it will not discriminate nor permit discrimination by its agents, servants or employees against any employee or applicant for employment with regard to hiring, tenure or employment, promotion, or any other terms, conditions or privileges of employment because of race, color, sex, religion, age, national origin, sex, ancestry, handicap or disability and will move aggressively as is hereinafter set forth to prevent same.
 - (i) In all publications or advertisements for employees to work at the job site covered by the Contract placed by or on behalf of the Respondent, the Respondent will state that all qualified applicants will receive consideration for employment without regard to race, color, religion, age, national origin, sex, ancestry, handicap or disability.
 - (ii) The Respondent will notify each labor union or workers' representative from whom it seeks workers of the Respondent's commitment as set forth in its proposal, and request that each union or workers' representative include minority group members and women among its referrals.
 - (iii) The Respondent will hire minority and female workers for the skilled and unskilled jobs required to perform the Contract in proportion to their availability in the relevant labor pools in the Philadelphia Metropolitan Statistical Area, or to their availability in its qualified applicant pool, whichever is greater.
 - (iv) The Respondent will post in conspicuous places available to its employees and to applicants for employment, a notice of fair practices to be provided by the Philadelphia Human Relations Commission.
 - (v) The Respondent will maintain a work environment free of harassment, intimidation and coercion, and will ensure that all on-site supervisory personnel are aware of and carry out Respondent's obligation to maintain such a working environment.
- (b) That it will identify on each certified payroll form submitted to the School District those of its employees who are minority group members and those who are female. As used here, "minority" means African American, Hispanic, Asian, or Native American. The School District shall at all times have access to work site and to the Respondent's employment records to assure compliance with this subsection.
- (c) That it will maintain on forms to be supplied by the School District, the name, race, sex, national origin, skill or craft, address, telephone number, and source of referral of each applicant for employment, which record shall show which applicants were hired.
- (d) (That in the event apprentices are hired in any skilled craft area, the Respondent will endeavor to hire equal numbers of culturally diverse male and female trainees in each skill area.

2. Non-Discrimination in Contracting

It is the policy of the School District of Philadelphia, that business concerns owned and controlled by minority group members and women shall have full and fair opportunity to participate in performance of contracts let by the School District. A Respondent's plan to joint venture with or subcontract to minority and woman-owned firms (M/WBEs) and/or to utilize M/WBEs as sources of supplies, equipment, or services will be a significant part of the evaluation of the Respondent's responsibility.

- (a) The Respondent will consider all proposals from potential M/WBE firms and document on the forms supplied by the School District, the reasons for not entering into a joint venture or subcontract with a M/WBE.
- (b) Respondent to this RFP shall employ the services of Sub-consultant(s), as necessary, to achieve combined Minority Owned Business Enterprise (MBE) and Woman Owned Business Enterprise (WBE) participation goals in a range of 15%-20% of the total amount of services provided. If the Firm is a MBE or WBE firm, then the Firm will have achieved the goal for that category. A non-MBE or WBE firm shall employ a MBE or WBE firm to achieve these goals.
- (c) The Respondent's agreement to meet the requirements of the Section is a material representation of fact upon which reliance will be placed if a contract is awarded. If it is later determined that the Respondent has not made a good faith effort to comply, within the School District's sole judgment, the School District may pursue available remedies, including suspension or debarment of the Respondent from future School District work as non-responsible.

3. Liability of Subcontractors

Any subcontractor of the Respondent shall have the same responsibilities and obligations as the Respondent to comply with the provisions of this Section and shall be subject to the same penalties for failure to comply as set forth below.

4. Penalties for Failure to Comply

It is hereby agreed that failure to comply and demonstrate a good faith effort to comply with the foregoing requirements shall constitute a substantial breach of the Contract.

Please sign below acknowledging and a Philadelphia.	agreeing to comply with the Anti-Discrimination Policy of the School District of
(Trade Name of Firm)	_ (seal)
(Signature of Owner or Partner)	_ (seal)

(Date)			

ATTACHMENT C SCHOOL DISTRICT OF PHILADELPHIA OFFICE OF PROCUREMENT SERVICES

MINORITY/WOMANOWNED BUSINESS ENTERPRISE(MWBE) PARTICIPATION PLAN FORM

I. Information in this section	n refers to the Prime Contractor/Vendor	
Company Name	Contact Perso	on:
Address:	Phone:	
City:	State:	Zip:
Fax:	E-mail:	
Owner:African-Americ	an,Hispanic,Asian,Native American,	Woman,Non-Profit,Caucasian,Other
Federal Tax ID	Certifying Agency:	Certification No.:
Bid Number or Subjectof Ro	esolution:	
	on refers to MWBE firms to be used in the performs	
	Owner:	
	Phone:	
		Zip:
Fax:	E-mail:	
Owner:African-Americ	an,Hispanic,Asian,NativeAmerican, _	Woman,Non-Profit,Caucasian,Other
Federal Tax ID	Certifying Agency:	Certification No.:
Description of Work:		
Dollar Value \$	Percentage of Total Contract	
Vendor Signature		
If no commitment, give reas	sons and supporting documentation(e.g., evidence o	f contacting MWREs)
I certify that the information	n provided is true and correc <u>t</u> Authorized Representativ	Date:

ATTACHMENT D

FEE PROPOSAL - PAGE 1 OF 3

Please acknowledge the following by signing where indicated below.

Method of Compensation

The method of compensation for this project shall be based on the Percentage of Construction Cost Method, see the "Professional Services Sample Contract." The final fee shall be adjusted based on the actual low construction bid amount. Hourly rates will be utilized for additional services.

Fee Schedule Based on % of Construction Value (page 2)

The Proposer's percentage of construction cost for the project shall be all-inclusive. The Proposer shall be entitled to payment for the authorized reimbursable expenses provided in the "Sample Professional Design Services Contract."

Project Design Team Personnel List with Hourly Rates (page 3)

The listing must include the hourly billable, all-inclusive wage rates for all people listed as design team personnel. These wage rates will be used to invoice for additional services performed. These hourly rates shall be fully loaded including benefits, overhead and profit. Please provide only one wage rate per position; do not use ranges. If ranges are used, the lower rate will be used for evaluation and if selected, will become the contract rate. Do not add positions.

Invoicing for services shall be limited to these individuals at the hourly rates indicated. Once the Prime Proposer enters into a contract with the SDP, any revisions or additions shall require prior approval by the SDP.

(Trade Name of Firm)	(Signature of Owner or Partner)

ATTACHMENT D

FEE PROPOSAL – PAGE 2 OF 3

PROPOSER'S FIRM:	
Provide the following:	
Project Construction Value	Proposed Fee
Over \$1,000,000	%

ATTACHMENT D

FEE PROPOSAL – PAGE 3 OF 3

PROPOSER'S I	FIRM:	

Name & Company	Position	Hourly Rate
Company	Key Personnel - Architectural	
•	Principal-In-Charge	\$
	Project Manager	\$
	Licensed Architect	\$
	Architectural Designer	\$
	Specifications Writer	\$
	Construction Administrator	\$
	Clerical	\$
Company	Key Personnel - Interior Design	
	Interior Designer	\$
Company	Key Personnel - Educational Planning	
	Educational Planner	\$
Company	Key Personnel - Civil Engineering	
	Principal-In-Charge	\$
	Licensed Civil Engineer	\$
	Licensed Landscape Architect	\$
	Project Engineer	
Company	Key Personnel - Structural Engineering	
, — — — — — — — — — — — — — — — — — — —	Principal-In-Charge	\$
	Licensed Structural Engineer	\$
	Project Engineer	\$
	Clerical	\$
Company	Key Personnel - MEP Engineering	
ı v	Principal-in-Charge	\$
	Project Manager	\$
	Licensed Mechanical Engineer	\$
	Licensed Electrical Engineer	\$
	Licensed Plumbing Engineer	\$
	Licensed Fire Detection Engineer	\$
	Licensed Fire Protection Engineer	\$
	Project Engineer	\$
	Cost Estimator	\$
	Clerical	\$
Company	Key Personnel - Cost Estimating	
	Senior Estimator	\$
	Estimator	\$
Company	Key Personnel – Elevator Consultant	
	Consultant	\$

APPENDIX A SITE ASSESSMENT REPORT

Facility Condition Assessment Summary Report

This report provides a summary of the Facility Condition Index (FCI) value of a school facility and select major building systems. The FCI calculation represents the cost of needed repairs divided by the replacement value. The FCI is a numerical value of condition and helps to identify the need for renewal or replacement of specific parts of the facility. The FCI is particularly useful when comparing similar facilities within the same portfolio.

Franklin High School

Governance DISTRICT Report Type High Address 550 N. Broad St. Enrollment 541 Philadelphia, Pa 19130 Grade Range '09-12'

Phone/Fax 215-299-4662 / 215-299-7285 Admissions Category Neighborhood

Website Www.Philasd.Org/Schools/Benfranklin Turnaround Model N/A

Building/System FCI Tiers

Facility Condition Index (FCI) = Cost of Assessed Deficiencies Replacement Value				
< 15%	15 to 25%	25 to 45%	45 to 60%	> 60%
		Buildings		
Minimal Current Capital Funding Required	Refurbish Systems in building	Replace Systems in building.	Building should be considered for major renovation.	Building should be considered for closing/replacement.
		Systems		
Perform routine maintenance on system	System requires minor repairs	System should be studied to determine repair vs. replacement.	System is nearing end of its life expectancy and should be considered for replacement	System should be replaced as part of the Capital Program

Building and Grounds

	FCI	Repair Costs	Replacement Cost
Overall	34.84%	\$51,452,949	\$147,679,380
Building	34.63 %	\$50,933,326	\$147,084,952
Grounds	87.42 %	\$519,623	\$594,428


Major Building Systems

Building System	System FCI	Repair Costs	Replacement Cost
Roof (Shows physical condition of roof)	62.19 %	\$2,311,503	\$3,716,836
Exterior Walls (Shows condition of the structural condition of the exterior facade)	02.42 %	\$290,605	\$12,008,041
Windows (Shows functionality of exterior windows)	191.11 %	\$14,614,001	\$7,646,767
Exterior Doors (Shows condition of exterior doors)	70.38 %	\$228,502	\$324,673
Interior Doors (Classroom doors)	07.57 %	\$80,703	\$1,066,089
Interior Walls (Paint and Finishes)	00.00 %	\$0	\$4,768,326
Plumbing Fixtures	04.92 %	\$181,901	\$3,697,391
Boilers	10.27 %	\$524,194	\$5,105,114
Chillers/Cooling Towers	53.86 %	\$3,605,372	\$6,694,556
Radiators/Unit Ventilators/HVAC	143.41 %	\$16,862,983	\$11,758,479
Heating/Cooling Controls	120.55 %	\$4,451,381	\$3,692,545
Electrical Service and Distribution	18.76 %	\$547,703	\$2,919,631
Lighting	12.46 %	\$1,300,619	\$10,435,560
Communications and Security (Cameras, Pa System and Fire Alarm)	07.20 %	\$281,401	\$3,908,186

School District of Philadelphia

S201001;Franklin HS

Final
Site Assessment Report
January 31, 2017



_		_	•	_		 	 _
_	- 1	•			~		_
Τа				. •		 	

Sit	te Executive Summary	4
Sit	ite Condition Summary	12
B2	<u>201001;Franklin HS</u>	14
	Executive Summary	14
	Condition Summary	15
	Condition Detail	16
	System Listing	17
	System Notes	19
	Renewal Schedule	20
	Forecasted Sustainment Requirement	23
	Condition Index Forecast by Investment Scenario	24
	Deficiency Summary By System	25
	Deficiency Summary By Priority	26
	Deficiency By Priority Investment	27
	Deficiency Summary By Category	28
	Deficiency Details By Priority	29
	Equipment Inventory Detail	50
<u>G2</u>	201001;Grounds	51
	Executive Summary	51
	Condition Summary	52
	Condition Detail	53
	System Listing	54
	System Notes	55
	Renewal Schedule	56
	Forecasted Sustainment Requirement	57
	Condition Index Forecast by Investment Scenario	58
	Deficiency Summary By System	59
	Deficiency Summary By Priority	60
	Deficiency By Priority Investment	61

Site Assessment Report

Deficiency Summary By Category	62
Deficiency Details By Priority	63
Equipment Inventory Detail	65
Glossary	66

Site Executive Summary

The organization of this report, as displayed in the Table of Contents, follows the structure of the associated eCOMET database. The overall node for each school campus begins with the letter "S", which indicates the "Site" label. Each Site is comprised of separate "Building" and "Grounds" nodes; their asset names begin with the letters "B" and "G" respectively. Information rolls up to the Site node from the Building and Grounds nodes. This Site report combines facility information with subsections for the Buildings And Grounds nodes.

The basis for the evaluation of condition is the functional systems and elements of a building and grounds organized according to the UNIFORMAT II Elemental Classification. The grouping of these systems and elements and applying a current replacement value to them develops a representative building cost model. Cost Models are typically developed for similar building types and functions. Evaluation of systems and their elements takes into account their current replacement values, life cycles, installation dates and next renewal dates. Systems and their elements that are within their useful lives are further evaluated to identify current deficient conditions that may have a significant impact on a system's or element's remaining service life, and to determine if they are beyond their predicted expected life. The system's or element's current replacement value is based on RS Means Commercial Cost Data.


Following are the cost model's system details for this facility. The Replacement Value is the amount needed to replace the property of the same present value. The Current Repair Amount, also known as Condition Needs, represents the budgeted contractor installed costs plus owner's soft costs for the repair, replacement or renewal for a component or system level deficiency. It excludes contributing costs for other components or systems that might also be associated with the corrective actions due to packaging the work. Facility Condition Index (FCI) is an industry-standard measurement calculated as the ratio of the repair costs to correct a facility's deficiencies to the facility's Current Replacement Value. Condition Index (CI) for a system is calculated as the sum of a the deficiencies divided by the sum of a system's Replacement Value (both values include soft-cost) expressed as a percentage ranging from 0% 100%.

242,293

Year Built: 1958
Last Renovation: 2015
Replacement Value: \$147,679,380
Repair Cost: \$51,452,948.76

Total FCI: 34.84 %

Total RSLI: 69.84 %



Description:

Facility Assessment, August 2015

School District of Philadelphia

Franklin High School

Gross Area (SF):

550 N. Broad St.

Philadelphia, PA 19130

242,293 SF / 1,556 Students / LN 03

The Franklin High School building is located at 550 N. Broad St. in Philadelphia, PA. The 6 story with full basement, approximately 242,293 square foot building was originally constructed in 1958. A 1 story addition with basement, containing auditorium, gym and supporting spaces was added in 1971. Portions of the basement are in the process of a complete renovation to accommodate vocational training classrooms.

Mr. Tom Sharer, Facility Area Coordinator provided input to the Parsons assessment team on current problems and planned renovation projects. Mr. Patrick Riley, building engineer, accompanied us on our tour of the school and provided limited information on the building systems and recent maintenance history.

STRUCTURAL/ EXTERIOR CLOSURE:

The original building typically rests on concrete foundations and concrete bearing walls that are not showing signs of settlement or cracking. There are no signs of moisture penetration through basement walls

The main structure consists typically of combination of cast-in-place concrete columns, beams and concrete slabs in the basement; and structural steel framing, columns and bar joists supporting concrete floor and roof slabs in the original building. The roof structure of the addition consists of steel trusses and purlins supporting precast roof deck panels. The superstructure is in good condition with the exception of fifth floor open play area columns and girders which show some concrete spalling and exposed rusting reinforcement.

The building envelope of the original building is typically aluminum framed curtain wall with double hung window inserts and granite spandrel panels at floor level. Some of the first floor window inserts have security screens in fair condition. End walls are stone clad masonry. Addition walls are typically face brick clad with CMU backup. In general, masonry is in fair to good condition with some missing mortar. The original curtain wall framing is corroded with deteriorated and missing sealant at insert panels' perimeter. Acrylic, single glazing is old and not energy efficient. Water penetration through walls has not been reported.

The main entrance and auditorium lobby wall is storefront type; stainless steel framed with aluminum framed window inserts and stainless steel glazed doors, in good condition.

The exterior service and egress doors are typically hollow metal doors and frames, painted. The doors are generally in poor condition with rusting leafs and frames in poor condition. Some doors have vision glazing with security screens. The loading dock has 2 overhead roll-up and 2 overhead sectional doors in very poor condition. Both sectional and one roll-up doors are not operational.

Roofing system is a built-up system approximately 20 years old; all roofing and flashing is typically in poor condition with deterioration of the built-up system; leaks have been reported.

INTERIORS:

The building partition wall types include painted CMU and glazed CMU; partitions between main office and hallway are hollow metal framed, storefront type, glazed with wire glass. Partitions are generally in good condition.

Interior doors are generally solid core wood doors, some glazed, with hollow metal frames, some doors are missing closers. Most doors do not have accessible handles. The doors leading to exit stairways and some toilets are hollow metal doors and frames in good condition.

Fittings include toilet accessories and toilet partitions, generally in poor condition, installed approximately in 1990, no accessible compartments; chalkboards in good condition. Handrails and ornamental metals are generally in good condition. Built-in cabinets and lockers are steel in fair condition. Interior identifying signage is typically directly painted on wall or door surfaces generally in poor condition with some signage missing.

The interior wall finishes are generally painted CMU. The auditorium lobby walls are clad with wood panels in good condition. Generally, paint is in good condition throughout the building.

Generally, most ceilings are exposed, painted. About 15% of ceilings in the building are 2x4 suspended acoustical panels and 1x1 tiles glued directly to underside of floor slab. The suspension system and tile are old and approaching the end of their useful life.

Flooring in typically is VAT (approximately 80% of floor area), generally in poor condition with tiles missing and separating from the substrate. The VAT tile flooring will need to be replaced as soon as practical. Library and principal's office and Culinary Arts suite has carpet in poor condition. Main lobby, portions of some corridors, and some toilets has terrazzo flooring in good condition. Gym has hardwood flooring in good condition.

Stair construction is generally concrete with cast iron, non-slip treads in good condition.

Institutional and Commercial equipment includes: stage equipment, generally in good condition; A/V equipment in very good condition; gym equipment – basketball backstops, scoreboards, bleachers, etc.; generally in good condition. Other equipment includes

kitchen equipment, generally in good condition.

Furnishings include fixed casework in classrooms, corridors and library, generally in fair to good condition; window shades/blinds, generally in fair condition; fixed auditorium seating is original, generally in fair condition.

CONVEYING SYSTEMS:

The building has two original, 14,600 lb traction elevators serving all floors; generally in fair condition; however, elevator cabins show signs of distress. The controls are functioning properly.

PLUMBING:

Plumbing Fixtures - Many of the original plumbing fixtures have been replaced. Fixtures in the restrooms on each floor consist of floor mounted flush valve water closets, wall hung urinals and lavatories with wheel handle faucets. A few of the fixtures are not in service. With repairs these fixtures should provide reliable service for the next 5-10 years.

Drinking fountains in the corridors and at the restrooms are a mixture of stainless steel and porcelain wall hung units. The units are beyond their service life and should be replaced; most are accessible type.

A mop basin is available in a janitor closet in the corridor on each floor for use by the janitorial staff.

The Kitchen has three sinks: a two compartment stainless steel prep sink with lever operated faucets and two three-compartment, stainless steel sinks with lever operated faucets, and integral grease traps. Chemicals are injected manually into the sanitizing basins.

Domestic Water Distribution - Two 4" city water services enter the building from N. Fifteenth Street near the intersection with Green Street. The 4" meters and valves are located in the sub-basement; reduced pressure backflow preventers are installed. The two services connect to a common supply main so that either service can supply the building. Three, no defunct, 30HP centrifugal pumps boost the pressure of the incoming water to supply the six story building. The pumps charge two large, horizontal open receiver tanks equipped with an air compressor to provide pneumatic charge. The Building Engineer reports that the original domestic booster system is no longer functional and pressure supplied by the city has increased to 65 psi. However, water to the building is still forced through the inactive pumps. The receiver tanks, pumps and air compressor should be removed and replaced by a modern domestic booster pump set equipped with variable speed drives. The original galvanize steel domestic hot and cold water distribution piping was replaced in the mid 1990's with copper piping and sweat fittings.

Three (3) Paloma instant hot water heaters, installed in 2006, are connected to two 3,000-4,000 gallon horizontal hot water storage tanks with two (2) 10HP circulating pumps to supply hot water for domestic use. The storage tanks have integral steam tube bundles and were the original source of domestic hot water, but the steam tubes are no longer in use. The units are located in the sub-basement, near the stairs from the basement level. One of the Paloma units appears inoperable and the other two are approaching the end of their service life. These tanks and the instantaneous water heaters should be removed and replaced with a single 400 gallon vertical storage tank supplied by two gas-fired hot water heaters within the next 1-3 years.

Sanitary Waste - The original storm and sanitary sewer piping is heavy weight cast iron with hub and spigot fittings. The 20" main sanitary sewer exits the building to the north from the sub-basement boiler room.

A sewage ejector pit located in sub-basement receives water from the sub-basement area. It has two 3HP self priming pumps. Significant amounts of rust can be seen on the pump system and it should be replaced to prevent flooding of the sub-basement. The pit is not sealed tightly, but should be.

The maintenance staff reported mostly minor problems with the sanitary waste piping systems. However, the sewer piping has been in service for nearly 60 years and will require more frequent attention from the maintenance staff as time passes. The District should hire a qualified contractor to examine the sanitary waste piping using video cameras to locate and replace any damaged piping and to further quantify the extent of potential failures.

Rain Water Drainage - The rain water drains from the roof are routed through mechanical chases in the building, connect to the storm sewer system in the sub-basement, and appear to be original. Some of the original galvanized piping has been repaired with HDPE piping and no-hub fittings. The drain piping should be inspected and repaired as necessary.

MECHANICAL:

Energy Supply - An 8" city gas service enters the building from Green Street. The meter is 6" and located the sub-basement. A gas pressure booster pump ensures adequate gas supply for the building.

The reserve oil supply is stored in a 2,500 gallon storage tank in the sub-basement. Duplex pumps located in the basement circulate oil through the system. Oil is used as a backup fuel and the District receives credit from the gas utility as an interruptible service. The current supply has been in storage for some time and should be tested for quality on a regular schedule. The actual condition of the fuel side is unknown.

Heat Generating Systems - Low pressure steam is generated at a maximum of 15 lbs/sq. in., typically 5-7 lbs/sq. in., by two 150 HP Weil McLain cast iron sectional boilers installed in 1997. Each boiler is equipped with a Power Flame burner designed to operate on natural gas or fuel oil. Combustion air makeup is supplied by louvers equipped with motorized dampers. Burner controls provide full modulation with electronic ignition and pressure atomization on oil. Burner oil pumps are loose and not driven by the fan motor. The gas train serving the boilers does have code required venting of the regulators and dual solenoid valves with venting of the chamber between. The Building Engineer reports the system loses a significant amount of condensate due to failed traps, which is made up with city water treated by a Neptune chemical treatment system. Cast iron sectional boilers have an anticipated service life of 35 years or more; these units have been in service approximately 18 years. The District should provide reliable service for the next 15 to 20 years.

The condensate receiver, along with a condensate return pump, is installed in a pit in the sub-basement. Another condensate return pump is located near the boilers. The main condensate receiver and pumps are badly corroded and should be replaced.

A steam trap survey for this building has not been conducted recently and traps are not serviced on a regular schedule. The District should conduct a steam trap survey to identify and replace failed traps passing live steam into the condensate piping system.

Distribution Systems - Steam piping is black steel with welded fittings. The condensate piping is black steel with threaded fittings. Steam and condensate piping mains from the sub-basement level run up through the building to the penthouse. The steam distribution piping has been in use well beyond its service life and will require more frequent attention from the maintenance staff to address pipe/valve failures as time passes. The District should hire a qualified contractor to examine the steam and condensate piping and perform additional testing to locate and replace any damaged piping and to further quantify the extent of potential failures. The District should budget for replacing this piping over the next 10 years.

Two steam to water shell and tube heat exchangers provide hydronic heating for the building. Four base-mounted pumps are located below the exchangers. Pumps P1 & P2 supply the North and South hydronic zones, respectively. The motor of pump P3 and the associated 3-way mixing valve have been removed; P4 is a backup unit. The pumps and control valves are failing and should be replaced. The tube bundles of the heat exchangers should be removed, inspected for damage and replaced if necessary, as they are beyond their anticipated service life. The heat exchangers are the original units installed in 1958 and have been in service more than 35 years. Shell-and-tube heat exchangers have an anticipated service life of 20 years. The heat exchanger tube bundles should be removed and inspected. If deficiencies are found, the tube bundles should be replaced.

Building water distribution piping is black steel with threaded fittings. The distribution piping is in poor condition. The piping has been in use beyond its service life and will require more frequent attention from the maintenance staff to address pipe/valve failures as time passes. The District should hire a qualified contractor to examine the distribution piping and perform additional testing to locate and replace any damaged piping and to further quantify the extent of potential failures. The District should budget for replacing this piping over the next 5 years.

Unit ventilators and fin tube radiators provide heating for the majority of classrooms, offices, and hallways. These units are well beyond their service life and original to the building. A new heating system should be installed to meet ventilation requirements and achieve more efficient operation. The new units should be designed for quiet operation and equipped with hot water coils, chilled water coils, and integral heat exchangers, where applicable, to introduce outdoor air to the building.

Air handling units provide conditioned air to specific spaces within the building. Air handling units AHU-1 thru AHU-8 were installed in 1999. Units AHU-1 and AHU-4 through AHU-8 are vertical units that serve the shops and labs on the basement level. That area was remodeled in 2015 for use as a Center for Advanced Manufacturing. These central station units are equipped with heating coils (HW/Steam), direct expansion (DX) cooling coils, and centrifugal supply fans. They are designed to supply a constant volume of conditioned air to the occupied spaces. Motorized OA/RA dampers in the ductwork provide economizer operation. AHU-1 and AHU-4 through AHU-8 have duct-mounted reheat coils that control space temperature. AHU-1 serves the rooms along the south corridor and the labs at the end of the center section. The HW heating coil of this unit is equipped with a circulating pump that provides freeze protection. AHU-4 is a similar unit that serves the rooms on the west corridor. AHU-6 serves the remaining rooms on this floor and has a steam heating coil. AHU-2 and AHU-3 are York units located in the mezzanine mechanical space above the lobby and serve the Auditorium; these units have steam coils for heating. The associated condensing units for these AHUs are located on the

low roof in the middle of the building; each unit is manufactured by Trane. Central station air handling units have an anticipated service life of 30 years, depending on the quality of their construction and proper maintenance. These units are within their anticipated service life and should provide reliable service for the 5-10 years.

An AHU, original to the building, in the penthouse supplies conditioned makeup air to the kitchen and Cafeteria on the 6th Floor. The heating coil of this unit has frozen at least once over the years and there are gaps in the pattern of fins where repairs were made. This unit should be replaced with a constant volume air handling unit with distribution ductwork and registers.

The Administration offices are served by unit ventilators, which provide heating and outdoor air only. Conditioned air should be provided the Administration offices by installing a fan coil air handling unit hung from the structure with outdoor air ducted to the unit from louvers in window openings.

Heating and ventilating units HV-1 through HV-13 are original Nesbitt units, in service for nearly 60 years. HV-1 (15 HP) & HV-2 (5 HP) located in the sub-basement boiler room are abandoned; these units originally served portions of the basement level. HV-4 located in the mezzanine mechanical room serves the lobby. HV-5 serves the boiler room on the sub-basement level in association with return/exhaust fan RE-13. HV-7 and HV-10 are large units located in the mezzanine mechanical room near the auditorium that serve the east gym and locker rooms, respectively. HV-8 and HV-9 are similar units located in the opposite mezzanine mechanical room that serves the west gym and locker rooms, respectively. HV-11 serves the mezzanine mechanical room above the lobby. HV-12 serves the NE electrical room on the basement level. HV-13 is a large unit that serves the high voltage electrical vault adjacent to the boiler room.

An original utility set fan installed in the penthouse exhausts air from the kitchen hood. Three original utility set fans located in the sub-basement mechanical room exhaust air from the restrooms and utility rooms. These fans have been in service for nearly 60 years. They are beyond their anticipated service life and should be replaced in the next 5-10 years.

A kitchen hood with integral fire suppression system operated by a Range Guard control system is installed above the gas fired cooking equipment. The system does not have a makeup air unit serving the hood. An automatic gas shutoff valve was installed with kitchen hood equipment.

Terminal & Package Units - Several of the classrooms in the school building have window air conditioning units that have an anticipated service life of only 10 years. Installing three 215 ton air-cooled chillers with pumps located in a mechanical room and chilled water distribution piping could supply more reliable air conditioning for the building with a much longer service life.

A Hyundai split system air conditioning system provided cooling to the LAN room. The installation date of this unit is unknown, but the unit is in poor condition. The anticipated service life of a split system air conditioner is 15 years. The district should budget to replace this unit within the next 3-5 years.

Controls & Instrumentation - The original pneumatic systems still provide basic control functions. Pneumatic room thermostats are intended to control the steam radiator and unit ventilator control valves. In reality the radiator and ventilator control valves are wide open and heating control is achieved via the boilers. Pneumatic control air is supplied from a duplex Quincy compressor and Hankison air dryer located in the boiler room. The pneumatic systems are beyond their service life and require too much attention from the maintenance staff. The original control valves and pneumatic actuators are beyond their service life and should be rebuilt or replaced. These controls should be converted to DDC.

A new building automation system (BAS) with modern DDC modules and communications network should be installed to serve the HVAC systems in this building to improve reliability and energy efficiency. An interface should be provided with the preferred system in use throughout the District.

Sprinklers - The majority of the school building is not covered by an automatic sprinkler system. A sprinkler system serving the basement and sub-basement levels only was installed in 2015. A 6" fire water line enters the building in the boiler room. Installing a sprinkler system with quick response type heads should reduce insurance costs by providing protection for the property investment. A fire pump may be required depending on the available city water pressure. The building does have standpipe in the stairwells.

Hose cabinets and stand pipe are located throughout the building. A 10 HP pump and horizontal receiver tank with compressed air pneumatic charge system, similar to the domestic water system, located in the sub-basement boiler room supplies the hose cabinets in the various functional areas, corridors and stairwells. This existing system was installed with the original construction. This system should be removed and replaced with sprinklers throughout the building.

ELECTRICAL:

Site Electrical Service- Electrical service to Benjamin Franklin High School is supplied by PECO Electric with two (2) 13.2 kV overhead lines. The first overhead service line is from poles on Green Street, and the second overhead line service is from 13.2KV pole line on Brandywine Street. The electrical service has recently been replaced (in 2015). A complete remodeling project for the Basement Floor is currently underway to convert the basement into a Career Technical Education center. The remodeling includes all new light fixtures and wiring devices for the space and replacement of panel-boards. The two electrical services feed a double-ended 1500 KVA, 13.2 kV -208V/120V, 3 phase, 4 wire substation. The Main Service Switchboard has air interrupter switches and 5000AT/5000AF main-tie-main circuit breakers. The new substation feeds existing panel-boards and equipment throughout the building.

Distribution System - Panel-boards PP-10 and PP-11 are located in the Boiler Room and are knife blade panel-boards with cartridge type fuses and exposed bus, and need to be replaced for safety considerations. All other panel-boards were observed to be circuit breaker type, most which are flush mounted in the corridors on each floor. These panel-boards have exceeded the end of their useful life, as recommended by Building Owners and Managers (BOMA) International, and should be replaced with panel-boards having more circuit breakers to accommodate additional branch circuits.

Receptacles- Many of the original receptacles in classrooms are 2-prong, ungrounded type and need to be replaced with 3-prong grounding type 15A or 20A, 120 volt duplex receptacles. Most of the classrooms have either two or three duplex receptacles. In some classrooms, additional 3-prong, grounding type duplex receptacles have been added using surface raceway. In many rooms, multiple outlet power strips have been added to power equipment where there were an insufficient number of outlets. Four (4) 20A, 120 volt duplex receptacles should be provided in each classroom and similar educational spaces.

Lighting - A majority of the lighting fixtures in corridors, classrooms and offices are surface or stem mounted, 4-foot, modular or wraparound fluorescent fixtures. Lay-in grid type, 2x4 foot troffers with acrylic lenses are provided in rooms with acoustical tile ceilings, such as the Main Office and Seminar Rooms on the Sixth Floor. Most classrooms have continuous rows of fixtures with two light switches. Corridors have wraparound fluorescent fixtures with 2 or 4 T8 lamps that are regularly spaced within the corridor. In other than corridors, most of the fixtures observed have T12 fluorescent lamps and are in poor condition, many with discolored or cracked lenses. There are only some rooms and areas where lighting fixtures have been have retrofitted with T8 energy saving lamps. Lighting fixtures need to be replaced in all classrooms on Floors 2 through 6 and in the cafeteria. Lighting fixtures in the gymnasium are stem mounted metal halide industrial fixtures with wire guards (total of 60 fixtures). Lighting fixtures in the main lobby on the First Floor are recessed metal halide downlights. A Hub Electric Company lighting control board is located on the Stage that provides dimming control of the recessed quartz downlights in the Auditorium and for the Stage lighting fixtures. There are also 4-foot fluorescent wraparound fixtures on the Stage for work-lights. Lighting fixtures in the Boiler Room and Sub-Basement Mechanical Rooms have a combination of stem mounted reflector dome incandescent fixtures and 4-foot, 2-lamp fluorescent industrial fixtures. Lamps in some of the incandescent fixtures have been replaced with compact fluorescent lamps. Lights on the exterior of the building are high pressure sodium floodlighting fixtures, all are in poor condition and should be replaced with LED floodlighting fixtures.

Fire Alarm - The fire alarm system consists of manual pull stations at egress doors, smoke detectors in the elevator lobby on all floors and audio/visual (strobe) annunciation appliances in most areas. The main fire alarm control panel (FACP) is a Simplex 4020 microprocessor-based, addressable panel, and is located in Main Office 126. There are three (3) Simplex 4009 N.A.C. Power Extender Panels that power the notification appliances in the building.

Telephone/LAN - Classrooms are typically provided with a telephone, clock/paging speaker assembly and wireless access panel for Wi -Fi service. Some classrooms have damaged or missing clock/paging speaker assemblies. Some classrooms are also provided with smart boards and ceiling mounted projectors. Speakers in corridors and most other spaces are wall mounted. Horn type speakers are used in the gymnasium and in mechanical rooms. The Simplex time control center for the clock and program system is located in Main Office 126. Staff reports that only one of the program schedules for this system still functions. The master time control center should be replaced.

Public Address/Sound System-There is no independent PA system. Overall the announcements are made using the phone system. There is no audio/visual intercom system at the main and secondary entrances or loading dock. An intercom system should be provided at these three locations for improved security and convenience. A separate sound system is provided in Auditorium 135. The sound system cabinet houses Crown Macro-Tech 1200 amplifiers, a Shure LX wireless microphone system and other sound system components. Speakers are ceiling mounted at the front of the stage and in the auditorium.

Security System - Video surveillance is provided by ceiling mounted cameras that are monitored at a central location. Cameras are located mainly in corridors, elevator lobbies, stairwells, cafeteria, auditorium, and main and secondary entrances.

TV System - There is no television system in the school.

Emergency Power System- An Onan 45 kW, 208/120 volt, 3 phase, 4 wire generator set and Onan automatic transfer switch (ATS) provides standby power for emergency lighting only. The generator set, ATS and standby power panelboard is located in Room 108.

The engine only has 585 hours of run time, and should have several hours of run time remaining before replacement.

Emergency lighting/Exit signs - Emergency lighting is provided by selected lighting fixtures throughout the building. Since school was in session, the assessor was not able to verify if the emergency lighting level met the code requirement of 1 foot-candle minimum in the path of egress. Exit signs were incandescent type. Many of the exit signs throughout the building were damaged, missing, or not illuminated. The exit signs need to be replaced with LED exit signs.

Lightning protection system - There is no lightning protection system on this building.

GROUNDS (SITE):

There is neither parking nor playground at the site. A small plaza at the building's main entrance is in poor condition, paving is cracked and deteriorated. The plaza covers a portion of the basement. Granite clad retaining walls are in very poor condition; stone panels are separating from the substrate, and stone coping is severely deteriorated. Cast alloy benches are damaged. There is no landscaping.

ACCESSIBILITY:

Generally, the building has an accessible route per ADA requirements. However, toilets are not equipped with accessible fixtures, and accessories, such as grab bars, and accessible partitions. Most of the doors in the building do not have ADA required door handles.

RECOMMENDATIONS:

- Repair cracks in masonry, replace missing mortar, tuck-point all masonry walls including panels covering columns and girders
- Epoxy patch spalled concrete columns and girders (5th floor play court)
- Install all new roofing system including insulation within next 5 to 10 years; tear-down existing roofing; install flashing, and counter flashing
- Replace all exterior service and egress doors including frames
- · Replace all overhead doors
- Replace curtain walls install new window inserts and spandrels within next 4 to 5 years
- Replace interior doors hardware for ADA accessibility
- Install new toilet partitions and accessories to comply with ADA requirements
- · Replace signage throughout the building
- Replace all VAT flooring including cove base within 5 years
- · Replace existing carpet
- · Replace all acoustical ceilings
- Refurbish elevator cabins
- Replace waterproofing membrane under exterior plaza paving
- Resurface entry plaza paving.
- Repair retaining walls, re-set stone cladding and replace stone coping
- Replace the wall hung drinking fountains in the corridors and at the restrooms. These units are beyond their service life and most are accessible type.
- Remove the existing domestic booster tanks and pumps and install a modern domestic water booster pump system.
- Remove and replace the hot two water storage tanks and the three instantaneous water heaters should with a single 400 gallon vertical storage tank supplied by two gas-fired hot water heaters within the next 1-3 years.
- Hire a qualified contractor to perform a detailed examination of the sanitary waste piping using visual inspection and video cameras to locate and replace any damaged piping and to further quantify the extent of potential failures.
- Replace existing sewage ejector system and piping in the basement as it appears beyond its useful service life.
- Hire a qualified contractor to perform a detailed examination of the rain water drainage piping using visual inspection and video cameras to locate and replace any damaged piping and to further quantify the extent of potential failures.
- Conduct a steam trap survey to identify and replace failed traps passing live steam into the condensate piping system.
- Replace the condensate receiver and pumps in the sub-basement level.
- Hire a qualified contractor to examine the steam and condensate piping in the boiler room, in service for nearly 70 years, and perform additional testing to locate and replace any damaged piping and to further quantify the extent of potential failures.
- Replace the two (2) steam to water shell and tube heat exchangers serving the building heating water system.
- Install four new hot water distribution pumps and associated valves in the sub-basement.
- Hire a qualified contractor to examine the distribution piping, in service for almost 60 years and damaged, and perform additional testing to locate and replace any damaged piping and to further quantify the extent of potential failures.
- · Remove the existing unit ventilators and fin tube radiators and install units with hot and chilled water coils and integral heat

exchangers to introduce outdoor air to the building.

- Provide ventilation for the Cafeteria by installing a constant volume air handling unit with distribution ductwork and registers.
- Provide ventilation for the administration offices by installing a fan coil air handling unit hung from the structure with outdoor air ducted to the unit from louvers in window openings.
- Replace four (4) existing exhaust fans in the penthouse and sub-basement serving the bathrooms and kitchen. Utilize the existing ductwork.
- Remove the window air conditioning units and install three (3) 215 ton air-cooled chillers with chilled water distribution piping
 and pumps located in a mechanical room to supply more reliable air conditioning for the building with a much longer
 service life.
- Replace the pneumatic controls for the HVAC systems with modern DDC modules, valves and actuators to improve reliability and energy efficiency. Provide a new building automation system (BAS) with communication interface to the preferred system in use throughout the District.
- Replace the original wet stand pipe installation with a fire protection sprinkler system with quick response type heads to reduce insurance costs by providing protection for the property. A fire pump may be required depending on the available city water pressure.
- Replace 600A Panelboard PP-10 and 400A Panelboard PP-11, both rated at 208/120 volt, 3 phas3, 4 wire located in the Boiler Room and in the Sub-Basement. Also, replace all flush-mounted panelboards in corridors and the gymnasium that have exceeded the end of their useful life, as recommended by Building Owners and Managers (BOMA) International (about 25 panelboards).
- Replace all 2-prong, ungrounded type duplex receptacles in classrooms and offices with 3-prong, grounding type duplex receptacles (about 110 duplex receptacles). Also, provide four (4) 20A, 120 volt duplex receptacles in each classroom and similar educational space so that there are an adequate number of outlets in these rooms (about 64 rooms).
- Replace lighting fixtures in all classrooms and similar spaces on Floors 2 through 6 and in the cafeteria (about 1088 fixtures). Also, replace lighting fixtures in the Boiler Room and Sub-Basement Mechanical Rooms with 4-foor industrial fluorescent fixtures with T8 lamps (Allowance for 24 fixtures). Replace thee (3) twin arm metal halide floodlighting fixtures outside the main entrance with LED floodlighting fixtures.
- Replace the master time control center in the Main Office and provide an allowance for 20 clock/paging speaker assemblies.
- Provide an audio/visual intercom system at the main and secondary entrances and loading dock entrance.
- Replace all exit signs in the building (except in Basement) with LED type exit signs. Estimate 48 single-face, 30 double-face.

Team:

Tm 4

Attributes:

Status:

General Attributes:

Active: Open Bldg Lot Tm: Lot 2 / Tm 4

Accepted by SDP

Site ID: S201001

Site Condition Summary

The Table below shows the CI and FCI for each major system shown at the UNIFORMAT classification Level II. Note that Systems with lower FCIs require less investment than systems with higher FCIs.


Current Investment Requirement and Condition by Uniformat Classification

UNIFORMAT Classification	RSLI%	FCI %	Current Repair
A10 - Foundations	43.00 %	0.00 %	\$0.00
A20 - Basement Construction	43.00 %	0.00 %	\$0.00
B10 - Superstructure	43.00 %	0.59 %	\$162,170.72
B20 - Exterior Enclosure	67.66 %	75.74 %	\$15,133,108.25
B30 - Roofing	64.56 %	62.19 %	\$2,311,503.21
C10 - Interior Construction	41.68 %	5.44 %	\$427,455.21
C20 - Stairs	45.23 %	0.00 %	\$0.00
C30 - Interior Finishes	73.17 %	2.98 %	\$452,472.91
D10 - Conveying	105.71 %	21.21 %	\$68,878.73
D20 - Plumbing	59.22 %	31.60 %	\$1,678,444.64
D30 - HVAC	94.23 %	83.64 %	\$25,443,930.30
D40 - Fire Protection	105.71 %	331.35 %	\$2,888,414.11
D50 - Electrical	95.38 %	13.38 %	\$2,366,947.87
E10 - Equipment	105.71 %	0.00 %	\$0.00
E20 - Furnishings	65.00 %	0.00 %	\$0.00
G20 - Site Improvements	105.64 %	92.75 %	\$329,726.83
G40 - Site Electrical Utilities	106.67 %	79.48 %	\$189,895.98
Totals:	69.84 %	34.84 %	\$51,452,948.76

Condition Deficiency Priority

Facility Name	Gross Area (S.F.)	FCI %	_	2 - Response Time (2-3 yrs)			_
B201001;Franklin HS	242,293	34.63	\$5,564,116.04	\$835,437.98	\$7,368,717.83	\$27,411,224.65	\$9,753,829.45
G201001;Grounds	17,300	87.42	\$0.00	\$0.00	\$397,789.93	\$121,832.88	\$0.00
Total:		34.84	\$5,564,116.04	\$835,437.98	\$7,766,507.76	\$27,533,057.53	\$9,753,829.45

Deficiencies By Priority



Budget Estimate Total: \$51,452,948.76

Executive Summary

Building condition is evaluated based on the functional systems and elements of a building and organized according to the UNIFORMAT II Elemental Classification. The grouping of these systems and elements and applying a current replacement value to them develops a representative building cost model. Cost Models are developed for similar building types and functions. Systems and their elements are evaluated based on their current replacement values, life cycles, installation dates and next renewal dates. Systems and their elements that are within their useful lives are further evaluated to identify current deficient conditions that may have a significant impact on a system's or element's remaining service life, and to determine if they are beyond their predicted expected life. The system's or element's current replacement value is based on RS Means Commercial Cost Data.

Following are the cost model's system details for this facility. The Replacement Value is the amount needed to replace the property of the same present value. The Current Repair Amount, also known as Condition Needs, represents the budgeted contractor installed costs plus owner's soft costs for the repair, replacement or renewal for a component or system level deficiency. It excludes contributing costs for other components or systems that might also be associated with the corrective actions due to packaging the work. Facility Condition Index (FCI) FCI is an industry-standard measurement of facility condition calculated as the ratio of the costs to correct a facility's deficiencies to the facility's Current Replacement Value. It ranges from 0% (new) to 100% (very poor). Condition Index (CI) is calculated as the sum of a renewable system's Remaining Service Life (RSL) divided by the sum of a system's Replacement Value (both values exclude soft-cost to simplify calculation updates) expressed as a percentage ranging from 100% (new) to 0% (expired).

Function:

Gross Area (SF): 242,293

Year Built: 1958

Last Renovation:

Replacement Value: \$147,084,952

Repair Cost: \$50,933,325.95

Total FCI: 34.63 %
Total RSLI: 69.70 %

Description:

Attributes:

General Attributes:

Active: Open Bldg ID: B201001

Sewage Ejector: Yes Status: Accepted by SDP

Site ID: S201001

Condition Summary

The Table below shows the CI and FCI for each major building system shown at the UNIFORMAT classification Level II. Note that Systems with lower FCIs require less investment than systems with higher FCIs.

UNIFORMAT Classification	RSLI %	FCI %	Current Repair Cost
A10 - Foundations	43.00 %	0.00 %	\$0.00
A20 - Basement Construction	43.00 %	0.00 %	\$0.00
B10 - Superstructure	43.00 %	0.59 %	\$162,170.72
B20 - Exterior Enclosure	67.66 %	75.74 %	\$15,133,108.25
B30 - Roofing	64.56 %	62.19 %	\$2,311,503.21
C10 - Interior Construction	41.68 %	5.44 %	\$427,455.21
C20 - Stairs	45.23 %	0.00 %	\$0.00
C30 - Interior Finishes	73.17 %	2.98 %	\$452,472.91
D10 - Conveying	105.71 %	21.21 %	\$68,878.73
D20 - Plumbing	59.22 %	31.60 %	\$1,678,444.64
D30 - HVAC	94.23 %	83.64 %	\$25,443,930.30
D40 - Fire Protection	105.71 %	331.35 %	\$2,888,414.11
D50 - Electrical	95.38 %	13.38 %	\$2,366,947.87
E10 - Equipment	105.71 %	0.00 %	\$0.00
E20 - Furnishings	65.00 %	0.00 %	\$0.00
Totals:	69.70 %	34.63 %	\$50,933,325.95

Condition Detail

This section of the report contains results of the Facility Condition Assessment. The building is separated into system components based on UNIFORMAT II classification. The columns in the System Listing table below represent the following:

- 1. System Code: A code that identifies the system.
- 2. System Description: A brief description of a system present in the building.
- 3. Unit Price \$: The unit price of the system.
- 4. UoM: The unit of measure for of the system.
- 5. Qty: The quantity for the system
- 6. Life: anticipated service life for the system based on Building Owners and Managers Association (BOMA) recommendations.
- 7. Year Installed: The date of system installation.
- 8. Calc Next Renewal Year: The date of system expiration based on the life, NR stands for non renewable.
- 9. Next Renewal Year: The suggested system expiration date by the assessor based on visual inspection.
- 10. CI: The Condition Index of the system.
- 11. FCI: The Facility Condition Index of the system.
- 12. RSL: Remaining Service Life.
- 13. eCR: eCOMET Condition Rating (not used).
- 14. Deficiency \$: The financial investment to repair/replace system.

System Listing

The System Listing table below lists each of the systems organized by their UNIFORMAT II classification. The assessment team was tasked with recording the most recent replacement year of each system, determining the remaining service life based on the theoretical life, and evaluating the condition to confirm the forecast next replacement year. The system listing is the basis for all data contained in the Building Assessment Report.

Additionally, a condition rating (eCR) based on the following guidelines is provided as observed at the time of the assessment.

- Excellent (E) No noticeable distress or damage. The entire system is free from observable defect.
- Very Good (VG) Overall no serviceability reduction for the entire system. No degradation of critical components and minor distress and defect noticeable for some but not non critical components within the system.
- Good (G) Slight or no serviceability reduction for the entire system. There may be noticeable defects for some non critical components and slight noticeable degradation of the critical components.
- Fair (F) Overall serviceability is degraded but adequate. There may be moderate deterioration for very few of the critical components and few of the non critical components may have severe degradation.
- Marginal (MA) Overall serviceability and reliability loss. Most if not all of the non critical components suffer from severe degradation and a few of the critical component may have severe degradation.
- Moderate (MO) Overall a significant serviceability loss. Most if not all the components have severe degradation with the reminder of the component showing visible distress.
- Very Poor (VP) Overall the system is barely functional. All of the components are severely degraded.
- Non-Functional (NF) Overall the system does not function with all the components having no serviceability and suffer from severe degradation.

System Code	System Description	Unit Price \$	UoM	Qty	Life	Year Installed	Calc Next Renewal Year	Next Renewal Year	RSLI%	FCI%	RSL	eCR	Deficiency \$	Replacement Value \$
A1010	Standard Foundations	\$31.89	S.F.	242,293	100	1958	2058		43.00 %	0.00 %	43			\$7,726,724
A1030	Slab on Grade	\$6.04	S.F.	242,293	100	1958	2058		43.00 %	0.00 %	43			\$1,463,450
A2010	Basement Excavation	\$5.09	S.F.	242,293	100	1958	2058		43.00 %	0.00 %	43			\$1,233,271
A2020	Basement Walls	\$11.58	S.F.	242,293	100	1958	2058		43.00 %	0.00 %	43			\$2,805,753
B1010	Floor Construction	\$97.37	S.F.	242,293	100	1958	2058		43.00 %	0.69 %	43		\$162,170.72	\$23,592,069
B1020	Roof Construction	\$16.42	S.F.	242,293	100	1958	2058		43.00 %	0.00 %	43			\$3,978,451
B2010	Exterior Walls	\$49.56	S.F.	242,293	100	1958	2058		43.00 %	2.42 %	43		\$290,605.25	\$12,008,041
B2020	Exterior Windows	\$31.56	S.F.	242,293	40	1958	1998	2057	105.00 %	191.11 %	42		\$14,614,001.43	\$7,646,767
B2030	Exterior Doors	\$1.34	S.F.	242,293	25	1958	1983	2040	100.00 %	70.38 %	25		\$228,501.57	\$324,673
B3010105	Built-Up	\$43.61	S.F.	79,545	20	1997	2017	2028	65.00 %	62.02 %	13		\$2,151,507.72	\$3,468,957
B3010120	Single Ply Membrane	\$44.73	S.F.	5,000	20	1971	1991	2027	60.00 %	71.54 %	12		\$159,995.49	\$223,650
B3010130	Preformed Metal Roofing	\$62.63	S.F.	0	30				0.00 %	0.00 %				\$0
B3010140	Shingle & Tile	\$44.73	S.F.	0	30				0.00 %	0.00 %				\$0
B3020	Roof Openings	\$0.10	S.F.	242,293	30	1997	2027	2028	43.33 %	0.00 %	13			\$24,229
C1010	Partitions	\$24.63	S.F.	242,293	100	1958	2058		43.00 %	0.00 %	43			\$5,967,677
C1020	Interior Doors	\$4.40	S.F.	242,293	40	1990	2030		37.50 %	7.57 %	15		\$80,702.57	\$1,066,089
C1030	Fittings	\$3.41	S.F.	242,293	40	1990	2030		37.50 %	41.97 %	15		\$346,752.64	\$826,219
C2010	Stair Construction	\$1.37	S.F.	242,293	100	1958	2058		43.00 %	0.00 %	43			\$331,941

Site Assessment Report - B201001;Franklin HS

System Code	System Description	Unit Price \$	UoM	Qty	Life	Year Installed	Calc Next Renewal Year	Next Renewal Year	RSLI%	FCI%	RSL	eCR	Deficiency \$	Replacement Value \$
C2020	Stair Finishes	\$0.45	S.F.	242,293	25	1958	1983	2028	52.00 %	0.00 %	13			\$109,032
C3010230	Paint & Covering	\$17.70	S.F.	242,293	10	2005	2015	2027	120.00 %	0.00 %	12			\$4,288,586
C3010231	Vinyl Wall Covering	\$0.00	S.F.	242,293	15	1958	1973	2027	80.00 %	0.00 %	12			\$0
C3010232	Wall Tile	\$1.98	S.F.	242,293	30	1958	1988	2035	66.67 %	0.00 %	20			\$479,740
C3020411	Carpet	\$8.54	S.F.	6,200	10	1958	1968	2020	50.00 %	0.00 %	5			\$52,948
C3020412	Terrazzo & Tile	\$88.36	S.F.	28,700	30	1958	1988	2030	50.00 %	0.00 %	15			\$2,535,932
C3020413	Vinyl Flooring	\$11.33	S.F.	135,400	20	1958	1978	2028	65.00 %	0.00 %	13			\$1,534,082
C3020414	Wood Flooring	\$26.07	S.F.	13,500	25	1958	1983	2028	52.00 %	0.00 %	13			\$351,945
C3020415	Concrete Floor Finishes	\$1.14	S.F.	10,000	50	1958	2008	2058	86.00 %	0.00 %	43			\$11,400
C3030	Ceiling Finishes	\$24.54	S.F.	242,293	30	1971	2001	2031	53.33 %	7.61 %	16		\$452,472.91	\$5,945,870
D1010	Elevators and Lifts	\$1.34	S.F.	242,293	35	1958	1993	2052	105.71 %	21.21 %	37		\$68,878.73	\$324,673
D2010	Plumbing Fixtures	\$15.26	S.F.	242,293	35	1995	2030	2035	57.14 %	4.92 %	20		\$181,900.56	\$3,697,391
D2020	Domestic Water Distribution	\$1.90	S.F.	242,293	25	1995	2020	2025	40.00 %	45.24 %	10		\$208,248.75	\$460,357
D2030	Sanitary Waste	\$2.61	S.F.	242,293	30	1958	1988	2047	106.67 %	183.40 %	32		\$1,159,772.85	\$632,385
D2040	Rain Water Drainage	\$2.15	S.F.	242,293	30	1958	1988	2025	33.33 %	24.67 %	10		\$128,522.48	\$520,930
D3020	Heat Generating Systems	\$21.07	S.F.	242,293	35	1997	2032		48.57 %	10.27 %	17		\$524,194.21	\$5,105,114
D3030	Cooling Generating Systems	\$27.63	S.F.	242,293	20	1999	2019	2037	110.00 %	53.86 %	22		\$3,605,372.21	\$6,694,556
D3040	Distribution Systems	\$48.53	S.F.	242,293	25	1958	1983	2042	108.00 %	143.41 %	27		\$16,862,983.19	\$11,758,479
D3050	Terminal & Package Units	\$13.09	S.F.	242,293	20	2005	2025	2028	65.00 %	0.00 %	13			\$3,171,615
D3060	Controls & Instrumentation	\$15.24	S.F.	242,293	20	1958	1978	2037	110.00 %	120.55 %	22		\$4,451,380.69	\$3,692,545
D4010	Sprinklers	\$7.94	S.F.	75,000	35			2052	105.71 %	485.04 %	37		\$2,888,414.11	\$595,500
D4020	Standpipes	\$1.14	S.F.	242,293	35			2052	105.71 %	0.00 %	37			\$276,214
D5010	Electrical Service/Distribution	\$12.05	S.F.	242,293	30	2001	2031	2047	106.67 %	18.76 %	32		\$547,703.10	\$2,919,631
D5020	Lighting and Branch Wiring	\$43.07	S.F.	242,293	20	1958	1978	2037	110.00 %	12.46 %	22		\$1,300,619.09	\$10,435,560
D5030	Communications and Security	\$16.13	S.F.	242,293	15	1958	1973	2022	46.67 %	7.20 %	7		\$281,400.56	\$3,908,186
D5090	Other Electrical Systems	\$1.76	S.F.	242,293	30	1958	1988	2047	106.67 %	55.63 %	32		\$237,225.12	\$426,436
E1020	Institutional Equipment	\$4.92	S.F.	242,293	35	1990	2025	2052	105.71 %	0.00 %	37			\$1,192,082
E1090	Other Equipment	\$11.35	S.F.	242,293	35	1990	2025	2052	105.71 %	0.00 %	37			\$2,750,026
E2010	Fixed Furnishings	\$2.17	S.F.	242,293	20	1958	1978	2028	65.00 %	0.00 %	13			\$525,776
								Total	69.70 %	34.63 %			\$50,933,325.95	\$147,084,952

System Notes

The facility description in the site executive summary contains an overview of each system. The notes listed below provide additional information on select systems found within the facility.

System: C3010 - Wall Finishes This system contains no images

Note:

Paint 90%

Wood paneling 10%

System: C3020 - Floor Finishes This system contains no images

Note:

VAT/ VCT 70% Tile/ terrazzo 15%

Carpet 3% Hardwood 7% Concrete 5%

Renewal Schedule

eCOMET forecasts future Capital Renewal funding needed to address expiring systems based on the Next Renewal year found in the Cost Models. A 3% annual inflation factor is applied to the costs for systems expiring in future years. The table below reflects recommended Capital Renewal funding needs over the next 10 years. Note: Cells with a zero value indicate systems for which renewal is not scheduled in that year.

Inflation Rate: 3%

System	Current Deficiencies	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	Total
Total:	\$50,933,326	\$0	\$0	\$0	\$0	\$67,520	\$0	\$5,287,234	\$0	\$0	\$1,450,643	\$57,738,723
* A - Substructure	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
A10 - Foundations	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
A1010 - Standard Foundations	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
A1030 - Slab on Grade	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
A20 - Basement Construction	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
A2010 - Basement Excavation	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
A2020 - Basement Walls	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
B - Shell	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
B10 - Superstructure	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
B1010 - Floor Construction	\$162,171	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$162,171
B1020 - Roof Construction	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
B20 - Exterior Enclosure	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
B2010 - Exterior Walls	\$290,605	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$290,605
B2020 - Exterior Windows	\$14,614,001	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$14,614,001
B2030 - Exterior Doors	\$228,502	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$228,502
B30 - Roofing	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
B3010 - Roof Coverings	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
B3010105 - Built-Up	\$2,151,508	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$2,151,508
B3010120 - Single Ply Membrane	\$159,995	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$159,995
B3010130 - Preformed Metal Roofing	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
B3010140 - Shingle & Tile	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
B3020 - Roof Openings	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C - Interiors	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C10 - Interior Construction	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C1010 - Partitions	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0

Site Assessment Report - B201001;Franklin HS

C1020 - Interior Doors	\$80,703	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$80,703
C1030 - Fittings	\$346,753	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$346,753
C20 - Stairs	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C2010 - Stair Construction	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C2020 - Stair Finishes	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C30 - Interior Finishes	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C3010 - Wall Finishes	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C3010230 - Paint & Covering	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C3010231 - Vinyl Wall Covering	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C3010232 - Wall Tile	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C3020 - Floor Finishes	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C3020411 - Carpet	\$0	\$0	\$0	\$0	\$0	\$67,520	\$0	\$0	\$0	\$0	\$0	\$67,520
C3020412 - Terrazzo & Tile	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C3020413 - Vinyl Flooring	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C3020414 - Wood Flooring	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C3020415 - Concrete Floor Finishes	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
C3030 - Ceiling Finishes	\$452,473	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$452,473
D - Services	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
D10 - Conveying	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
D1010 - Elevators and Lifts	\$68,879	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$68,879
D20 - Plumbing	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
D2010 - Plumbing Fixtures	\$181,901	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$181,901
D2020 - Domestic Water Distribution	\$208,249	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$680,549	\$888,797
D2030 - Sanitary Waste	\$1,159,773	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$1,159,773
D2040 - Rain Water Drainage	\$128,522	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$770,095	\$898,617
D30 - HVAC	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
D3020 - Heat Generating Systems	\$524,194	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$524,194
D3030 - Cooling Generating Systems	\$3,605,372	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$3,605,372
D3040 - Distribution Systems	\$16,862,983	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$16,862,983
D3050 - Terminal & Package Units	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
D3060 - Controls & Instrumentation	\$4,451,381	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$4,451,381
D40 - Fire Protection	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
D4010 - Sprinklers	\$2,888,414	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$2,888,414


Site Assessment Report - B201001;Franklin HS

D4020 - Standpipes	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
D50 - Electrical	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
D5010 - Electrical Service/Distribution	\$547,703	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$547,703
D5020 - Lighting and Branch Wiring	\$1,300,619	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$1,300,619
D5030 - Communications and Security	\$281,401	\$0	\$0	\$0	\$0	\$0	\$0	\$5,287,234	\$0	\$0	\$0	\$5,568,634
D5090 - Other Electrical Systems	\$237,225	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$237,225
E - Equipment & Furnishings	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
E10 - Equipment	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
E1020 - Institutional Equipment	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
E1090 - Other Equipment	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
E20 - Furnishings	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
E2010 - Fixed Furnishings	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0

^{*} Indicates non-renewable system

Forecasted Sustainment Requirement

The following chart shows the current building deficiencies and forecasting sustainment requirements over the next ten years.



10 Year FCI Forecast by Investment Scenario

The chart below illustrates the effect of various investment levels on the building FCI for the next 10 years. The levels of investment shown below include:


- Current FCI: a variable investment amount based on renewing expired systems to maintain the current FCI for the building
- 2% Investment: an annual investment of 2% of the replacement value of the building, escalated for inflation
- 4% Investment: an annual investment of 4% of the replacement value of the building, escalated for inflation

Facility Investment vs. FCI Forecast \$70,000,000 80.0 % \$60,000,000 70.0 % \$50,000,000 Investment Amount - 60.0 % \$40,000,000 Ξ \$30,000,000 - 50.0 % \$20,000,000 - 40.0 % \$10,000,000 30.0 % \$0 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 Current Investment Amount/FCI 2% Investment Amount/FCI 4% Investment Amount/FCI

	Investment Amount	2% Investm	ent	4% Investm	ent
Year	Current FCI - 34.63%	Amount	FCI	Amount	FCI
2016	\$0	\$3,029,950.00	32.63 %	\$6,059,900.00	30.63 %
2017	\$62,589,685	\$3,120,849.00	70.74 %	\$6,241,697.00	66.74 %
2018	\$0	\$3,214,474.00	68.74 %	\$6,428,948.00	62.74 %
2019	\$0	\$3,310,908.00	66.74 %	\$6,621,816.00	58.74 %
2020	\$67,520	\$3,410,235.00	64.78 %	\$6,820,471.00	54.78 %
2021	\$0	\$3,512,542.00	62.78 %	\$7,025,085.00	50.78 %
2022	\$5,287,234	\$3,617,919.00	63.70 %	\$7,235,838.00	49.70 %
2023	\$0	\$3,726,456.00	61.70 %	\$7,452,913.00	45.70 %
2024	\$0	\$3,838,250.00	59.70 %	\$7,676,500.00	41.70 %
2025	\$1,450,643	\$3,953,398.00	58.44 %	\$7,906,795.00	38.44 %
Total:	\$69,395,082	\$34,734,981.00		\$69,469,963.00	

Deficiency Summary by System


Current deficiencies included assemblies that have reached or exceeded their design life or components of the assemblies that are in need of repair. Assemblies that have reached their design life are identified as current deficiencies and assigned the distress 'Beyond Useful Life'. The following chart lists all current deficiencies associated with this facility.



Budget Estimate Total: \$50,933,325.95

Deficiency Summary by Priority

The following chart shows the total repair costs broken down by priority. Assessors assigned deficiencies within eCOMET to one of the following priority categories:



Budget Estimate Total: \$50,933,325.95


Deficiency By Priority Investment Table

The table below shows the current investment cost grouped by deficiency priority and building system.

System Code	System Description	1 - Response Time (< 2 yr)	2 - Response Time (2-3 yrs)	3 - Response Time (3-4 yrs)	4 - Response Time (4-5 yrs)	5 - Response Time (> 5 yrs)	Total
B1010	Floor Construction	\$0.00	\$0.00	\$162,170.72	\$0.00	\$0.00	\$162,170.72
B2010	Exterior Walls	\$0.00	\$0.00	\$0.00	\$290,605.25	\$0.00	\$290,605.25
B2020	Exterior Windows	\$0.00	\$0.00	\$0.00	\$14,614,001.43	\$0.00	\$14,614,001.43
B2030	Exterior Doors	\$0.00	\$0.00	\$64,569.80	\$163,931.77	\$0.00	\$228,501.57
B3010105	Built-Up	\$2,151,507.72	\$0.00	\$0.00	\$0.00	\$0.00	\$2,151,507.72
B3010120	Single Ply Membrane	\$0.00	\$0.00	\$159,995.49	\$0.00	\$0.00	\$159,995.49
C1020	Interior Doors	\$0.00	\$0.00	\$0.00	\$80,702.57	\$0.00	\$80,702.57
C1030	Fittings	\$0.00	\$0.00	\$0.00	\$292,570.14	\$54,182.50	\$346,752.64
C3030	Ceiling Finishes	\$0.00	\$0.00	\$0.00	\$0.00	\$452,472.91	\$452,472.91
D1010	Elevators and Lifts	\$0.00	\$0.00	\$68,878.73	\$0.00	\$0.00	\$68,878.73
D2010	Plumbing Fixtures	\$0.00	\$0.00	\$181,900.56	\$0.00	\$0.00	\$181,900.56
D2020	Domestic Water Distribution	\$0.00	\$88,711.24	\$0.00	\$0.00	\$119,537.51	\$208,248.75
D2030	Sanitary Waste	\$0.00	\$108,227.46	\$1,051,545.39	\$0.00	\$0.00	\$1,159,772.85
D2040	Rain Water Drainage	\$0.00	\$0.00	\$128,522.48	\$0.00	\$0.00	\$128,522.48
D3020	Heat Generating Systems	\$524,194.21	\$0.00	\$0.00	\$0.00	\$0.00	\$524,194.21
D3030	Cooling Generating Systems	\$0.00	\$0.00	\$0.00	\$0.00	\$3,605,372.21	\$3,605,372.21
D3040	Distribution Systems	\$0.00	\$638,499.28	\$3,465,587.35	\$11,688,012.93	\$1,070,883.63	\$16,862,983.19
D3060	Controls & Instrumentation	\$0.00	\$0.00	\$0.00	\$0.00	\$4,451,380.69	\$4,451,380.69
D4010	Sprinklers	\$2,888,414.11	\$0.00	\$0.00	\$0.00	\$0.00	\$2,888,414.11
D5010	Electrical Service/Distribution	\$0.00	\$0.00	\$547,703.10	\$0.00	\$0.00	\$547,703.10
D5020	Lighting and Branch Wiring	\$0.00	\$0.00	\$1,300,619.09	\$0.00	\$0.00	\$1,300,619.09
D5030	Communications and Security	\$0.00	\$0.00	\$0.00	\$281,400.56	\$0.00	\$281,400.56
D5090	Other Electrical Systems	\$0.00	\$0.00	\$237,225.12	\$0.00	\$0.00	\$237,225.12
	Total:	\$5,564,116.04	\$835,437.98	\$7,368,717.83	\$27,411,224.65	\$9,753,829.45	\$50,933,325.95

Deficiency Summary by Category

The following chart shows the total repair costs broken down by deficiency categories. Assessors assigned deficiencies to one of the following categories:



Budget Estimate Total: \$50,933,325.95

Deficiency Details by Priority

The deficiency detail notes listed below provide additional information on identified deficiencies found within the facility.

Priority 1 - Response Time (< 2 yr):

System: B3010105 - Built-Up



Location: Exterior

Distress: Building Envelope Integrity

Category: 3 - Operations / Maint.

Priority: 1 - Response Time (< 2 yr)

Correction: Remove and Replace Built Up Roof

Qty: 63,500.00

Unit of Measure: S.F.

Estimate: \$2,151,507.72

Assessor Name: System

Date Created: 10/14/2015

Notes: Install all new roofing system including insulation within next 5 to 10 years; tear-down existing roofing; install flashing, and counter flashing

System: D3020 - Heat Generating Systems



Location: Sub-basement

Distress: Failing

Category: 3 - Operations / Maint.

Priority: 1 - Response Time (< 2 yr)

Correction: Replace pump, base-mounted, end suction

HHW (5" size, 15 HP, to 1000 GPM)

Qty: 4.00

Unit of Measure: Ea.

Estimate: \$524,194.21

Assessor Name: System

Date Created: 09/21/2015

Notes: Replace four (4) existing hot water distribution pumps and associated valves in the sub-basement.

System: D4010 - Sprinklers



Location: Throughout building

Distress: Life Safety / NFPA / PFD

Category: 1 - Health & Safety

Priority: 1 - Response Time (< 2 yr)

Correction: Install a fire protection sprinkler system

Qty: 201,910.00

Unit of Measure: S.F.

Estimate: \$2,888,414.11

Assessor Name: System

Date Created: 09/22/2015

Notes: Replace the original wet stand pipe installation with a fire protection sprinkler system with quick response type heads to reduce insurance costs by providing protection for the property. A fire pump may be required depending on the available city water pressure.

Priority 2 - Response Time (2-3 yrs):

System: D2020 - Domestic Water Distribution



Location: Boiler room

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 2 - Response Time (2-3 yrs)

Correction: Replace instantaneous water heater

Qty: 1.00

Unit of Measure: Ea.

Estimate: \$88,711.24

Assessor Name: System

Date Created: 09/21/2015

Notes: Remove and replace the hot two water storage tanks and the three instantaneous water heaters should with a single 400 gallon vertical storage tank supplied by two gas-fired hot water heaters within the next 1-3 years.

System: D2030 - Sanitary Waste



Location: Boiler room

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 2 - Response Time (2-3 yrs)

Correction: Replace sanitary sewage ejector pit and pumps.

(60" dia.)

Qty: 2.00

Unit of Measure: Ea.

Estimate: \$108,227.46

Assessor Name: System

Date Created: 09/21/2015

Notes: Replace existing sewage ejector system and piping in the basement as it appears beyond its useful service life.

System: D3040 - Distribution Systems



Location: Sub-basement

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 2 - Response Time (2-3 yrs)

Correction: Replace shell and tube hydronic heat exchanger

(240 gpm)

Qty: 2.00

Unit of Measure: Ea.

Estimate: \$401,511.82

Assessor Name: System

Date Created: 09/22/2015

Notes: Replace the two (2) steam to water shell and tube heat exchangers serving the building heating water system.

System: D3040 - Distribution Systems



Location: Penthouse and Sub-basement

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 2 - Response Time (2-3 yrs)

Correction: Replace utility set exhaust fan (5 HP)

Qty: 4.00

Unit of Measure: Ea.

Estimate: \$189,196.36

Assessor Name: System

Date Created: 09/22/2015

Notes: Replace four (4) existing exhaust fans in the penthouse and sub-basement serving the bathrooms and kitchen. Utilize the existing ductwork.

System: D3040 - Distribution Systems



Location: Sub-basement

Distress: Damaged

Category: 3 - Operations / Maint.

Priority: 2 - Response Time (2-3 yrs)

Correction: Replace Condensate Receiver Pump Set

Qty: 1.00

Unit of Measure: Ea.

Estimate: \$47,791.10

Assessor Name: System

Date Created: 09/21/2015

Notes: Replace the condensate receiver and pumps in the sub-basement level.

Priority 3 - Response Time (3-4 yrs):

System: B1010 - Floor Construction



Location: Exterior

Distress: Damaged

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Repair rebar and epoxy grout exposed rebar on

the underside of floors and floor beams

Qty: 2,000.00

Unit of Measure: S.F.

Estimate: \$162,170.72

Assessor Name: System

Date Created: 10/14/2015

Notes: Epoxy patch spalled concrete columns and girders (5th floor play court)

System: B2030 - Exterior Doors



Location: Exterior

Distress: Failing

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Remove and replace overhead door - pick the

closest type and size and add for the operator if

required

Qty: 4.00

Unit of Measure: Ea.

Estimate: \$64,569.80

Assessor Name: System

Date Created: 10/14/2015

Notes: Replace all overhead doors

System: B3010120 - Single Ply Membrane



Location: Exterior/ ground level

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Remove and replace concrete deck topping

including remove and replace waterproofing membrane - add for epoxy coating if required

by inserting the SF in the estimate

Qty: 5,000.00

Unit of Measure: S.F.

Estimate: \$159,995.49

Assessor Name: System

Date Created: 06/23/2015

Notes: Replace waterproofing membrane under exterior plaza paving

NOTE: paving replacement deficiency covered under G201001; Grounds

System: D1010 - Elevators and Lifts



Location: Interior

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Upgrade passenger elevator cab and controls

Qty: 1.00

Unit of Measure: Ea.

Estimate: \$68,878.73

Assessor Name: System

Date Created: 10/15/2015

Notes: Refurbish elevator cabins

System: D2010 - Plumbing Fixtures



Location: Corridors

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Remove and Replace Water Fountains - without

ADA new recessed alcove

Qty: 24.00

Unit of Measure: Ea.

Estimate: \$181,900.56

Assessor Name: System

Date Created: 09/21/2015

Notes: Replace the wall hung drinking fountains in the corridors and at the restrooms. These units are beyond their service life and most are accessible type.

System: D2030 - Sanitary Waste



Location: Throughout building

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Inspect sanitary waste piping and replace

damaged sections. (+200KSF)

Qty: 242,293.00

Unit of Measure: S.F.

Estimate: \$1,051,545.39

Assessor Name: System

Date Created: 09/21/2015

Notes: Hire a qualified contractor to perform a detailed examination of the sanitary waste piping using visual inspection and video cameras to locate and replace any damaged piping and to further quantify the extent of potential failures.

System: D2040 - Rain Water Drainage



Location: Throughout building

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Replace roof drains - per drain including piping

Qty: 5.00

Unit of Measure: Ea.

Estimate: \$128,522.48

Assessor Name: System

Date Created: 09/22/2015

Notes: Hire a qualified contractor to perform a detailed examination of the rain water drainage piping using visual inspection and video cameras to locate and replace any damaged piping and to further quantify the extent of potential failures.

System: D3040 - Distribution Systems



Location: Throughout building

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Perform testing to identify and replace

damaged steam and condensate piping.

Qty: 242,293.00

Unit of Measure: S.F.

Estimate: \$2,292,182.14

Assessor Name: System

Date Created: 09/21/2015

Notes: Hire a qualified contractor to examine the distribution piping, in service for almost 60 years and damaged, and perform additional testing to locate and replace any damaged piping and to further quantify the extent of potential failures.

System: D3040 - Distribution Systems



Location: Throughout building

Distress: Failing

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Conduct a steam trap survey and replace failed

units.

Qty: 242,293.00

Unit of Measure: S.F.

Estimate: \$794,990.22

Assessor Name: System

Date Created: 09/21/2015

Notes: Conduct a steam trap survey to identify and replace failed traps passing live steam into the condensate piping system.

System: D3040 - Distribution Systems



Location: Throughout building

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Perform testing to identify and replace

damaged steam and condensate piping.

Qty: 40,000.00

Unit of Measure: S.F.

Estimate: \$378,414.99

Assessor Name: System

Date Created: 09/21/2015

Notes: Hire a qualified contractor to examine the steam and condensate piping in the boiler room, in service for nearly 70 years, and perform additional testing to locate and replace any damaged piping and to further quantify the extent of potential failures.

System: D5010 - Electrical Service/Distribution



Location: Corridors and Gymnasium

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Add Panelboard

Qty: 1.00

Unit of Measure: Ea.

Estimate: \$436,950.60

Assessor Name: System

Date Created: 06/20/2015

Notes: Replace all flush-mounted panelboards in corridors and the gymnasium that have exceeded the end of their useful life, as recommended by Building Owners and Managers (BOMA) International. Also, replace panelboard feeder conductors. Estimate 25 panelboards

System: D5010 - Electrical Service/Distribution



Location: Boiler Room and Sub-Basement

Distress: Failing

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Add Panelboard

Qty: 1.00

Unit of Measure: Ea.

Estimate: \$110,752.50

Assessor Name: System

Date Created: 06/17/2015

Notes: Replace 600A Panelboard PP-10 and 400A Panelboard PP-11, both rated at 208/120 volt, 3 phas3, 4 wire located in the Boiler Room and in the Sub-Basement.

System: D5020 - Lighting and Branch Wiring



Location: Classrooms

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Replace lighting fixtures

Qty: 1,088.00

Unit of Measure: Ea.

Estimate: \$917,096.66

Assessor Name: System

Date Created: 06/20/2015

Notes: Replace lighting fixtures in all classrooms and similar spaces on Floors 2 through 6 and in the cafeteria. Estimate 1088 fixtures.

System: D5020 - Lighting and Branch Wiring



Location: Classrooms

Distress: Building / MEP Codes

Category: 2 - Code Compliance

Priority: 3 - Response Time (3-4 yrs)

Correction: Replace Wiring Devices (SF) - surface mounted

conduit and boxes

Qty: 110.00

Unit of Measure: S.F.

Estimate: \$206,043.60

Assessor Name: System

Date Created: 06/20/2015

Notes: Replace all 2-prong, ungrounded type duplex receptacles in classrooms and offices with 3-prong, grounding type duplex receptacles. Estimate 110 duplex receptacles need to be replaced.

System: D5020 - Lighting and Branch Wiring



Location: Classrooms

Distress: Building / MEP Codes

Category: 2 - Code Compliance

Priority: 3 - Response Time (3-4 yrs)

Correction: Add wiring device

Qty: 256.00

Unit of Measure: Ea.


Estimate: \$177,478.83

Assessor Name: System

Date Created: 06/20/2015

Notes: Provide an additional four (4) 20A, 120 volt duplex receptacles in each classroom and similar educational space so that there are an adequate number of outlets in these rooms. Estimate 64 rooms,

System: D5090 - Other Electrical Systems



Notes: Install new Exit lights and emergency lights

Location: throughout the building

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Add Emergency/Exit Lighting

Qty: 1.00

Unit of Measure: Ea.


Estimate: \$237,225.12

Assessor Name: System

Date Created: 10/15/2015

Priority 4 - Response Time (4-5 yrs):

System: B2010 - Exterior Walls



Location: Exterior

Distress: Building Envelope Integrity

Category: 3 - Operations / Maint.

Priority: 4 - Response Time (4-5 yrs)

Correction: Repair cracks in masonry - replace missing

mortar and repoint - SF of wall area

Qty: 9,000.00

Unit of Measure: S.F.

Estimate: \$290,605.25

Assessor Name: System

Date Created: 10/14/2015

Notes: Repair cracks in masonry, replace missing mortar, tuck-point – all masonry walls including panels covering columns and girders

System: B2020 - Exterior Windows



Location: Exterior

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 4 - Response Time (4-5 yrs)

Correction: Remove and replace curtain wall systems - SF

of curtain wall area

Qty: 89,200.00

Unit of Measure: S.F.

Estimate: \$14,614,001.43

Assessor Name: System

Date Created: 10/14/2015

Notes: Replace curtain walls install new window inserts and spandrels within next 4 to 5 years

System: B2030 - Exterior Doors



Location: Exterior

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 4 - Response Time (4-5 yrs)

Correction: Remove and replace exterior doors - per leaf

Qty: 18.00

Unit of Measure: Ea.

Estimate: \$163,931.77

Assessor Name: System

Date Created: 10/14/2015

Notes: Replace all exterior service and egress doors including frames

System: C1020 - Interior Doors



Notes: Replace interior doors hardware for ADA accessibility

Location: interior

Distress: Accessibility

Category: 2 - Code Compliance

Priority: 4 - Response Time (4-5 yrs)

Correction: Replace door knobs with compliant lever type

Qty: 145.00

Unit of Measure: Ea.

Estimate: \$80,702.57

Assessor Name: System

Date Created: 10/14/2015

System: C1030 - Fittings



Location: Interior

Distress: Accessibility

Category: 2 - Code Compliance

Priority: 4 - Response Time (4-5 yrs)

Correction: Remove and replace toilet partitions

Qty: 114.00

Unit of Measure: Ea.

Estimate: \$292,570.14

Assessor Name: System

Date Created: 10/15/2015

Notes: Install new toilet partitions and accessories to comply with ADA requirements

System: D3040 - Distribution Systems



Location: Classrooms

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 4 - Response Time (4-5 yrs)

Correction: Replace the existing unit ventilators with new

units designed to provide adequate ventilation per ASHRAE Std 62 - insert the SF of bldg. in

the qty.

Qty: 242,293.00

Unit of Measure: S.F.

Estimate: \$11,688,012.93

Assessor Name: System

Date Created: 09/21/2015

Notes: Remove the existing unit ventilators and fin tube radiators and install units with hot and chilled water coils and integral heat exchangers to introduce outdoor air to the building.

System: D5030 - Communications and Security



Location: Throughout the building

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 4 - Response Time (4-5 yrs)

Correction: Add/Replace Clock System or Components

Qty: 0.00

Unit of Measure: Ea.

Estimate: \$281,400.56

Assessor Name: System

Date Created: 10/15/2015

Notes: Install new clock system

Priority 5 - Response Time (> 5 yrs):

System: C1030 - Fittings



Location: Interior

Distress: Inadequate

Category: 4 - Capital Improvement

Priority: 5 - Response Time (> 5 yrs)

Correction: Replace missing or damaged signage - insert

the number of rooms

Qty: 200.00

Unit of Measure: Ea.

Estimate: \$54,182.50

Assessor Name: System

Date Created: 10/15/2015

Notes: Replace signage throughout the building

System: C3030 - Ceiling Finishes



Location: Interior

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 5 - Response Time (> 5 yrs)

Correction: Remove and replace suspended acoustic

ceilings - lighting not included

Qty: 30,000.00

Unit of Measure: S.F.

Estimate: \$452,472.91

Assessor Name: System

Date Created: 10/15/2015

Notes: Replace all acoustical ceilings

System: D2020 - Domestic Water Distribution



Location: Sub-basement

Distress: Obsolete

Category: 3 - Operations / Maint.

Priority: 5 - Response Time (> 5 yrs)

Correction: Replace duplex domestic booster pump set (5

HP)

Qty: 1.00

Unit of Measure: Ea.

Estimate: \$119,537.51

Assessor Name: System

Date Created: 09/22/2015

Notes: Remove the existing domestic booster tanks and pumps and install a modern domestic water booster pump system.

System: D3030 - Cooling Generating Systems



Location: Throughout building

Distress: Inadequate

Category: 4 - Capital Improvement

Priority: 5 - Response Time (> 5 yrs)

Correction: Install chilled water system with distribution

piping and pumps. (+250KSF)

Qty: 242,293.00

Unit of Measure: S.F.


Estimate: \$3,605,372.21

Assessor Name: System

Date Created: 09/21/2015

Notes: Remove the window air conditioning units and install three (3) 215 ton air-cooled chillers with chilled water distribution piping and pumps located in a mechanical room to supply more reliable air conditioning for the building with a much longer service life.

System: D3040 - Distribution Systems



Location: Administration

Distress: Building / MEP Codes

Category: 2 - Code Compliance

Priority: 5 - Response Time (> 5 yrs)

Correction: Install HVAC unit for Administration (2000

students).

Qty: 1,556.00

Unit of Measure: Pr.

Estimate: \$673,473.57

Assessor Name: System

Date Created: 09/22/2015

Notes: Provide ventilation for the administration offices by installing a fan coil air handling unit hung from the structure with outdoor air ducted to the unit from louvers in window openings.

System: D3040 - Distribution Systems



Location: Cafeteria

Distress: Building / MEP Codes

Category: 2 - Code Compliance

Priority: 5 - Response Time (> 5 yrs)

Correction: Install HVAC unit for Cafeteria (850 students).

Qty: 850.00

Unit of Measure: Pr.

Estimate: \$397,410.06

Assessor Name: System

Date Created: 09/22/2015

Notes: Provide ventilation for the Cafeteria by installing a constant volume air handling unit with distribution ductwork and registers.

System: D3060 - Controls & Instrumentation



Location: Throughout building

Distress: Inadequate

Category: 4 - Capital Improvement

Priority: 5 - Response Time (> 5 yrs)

Correction: Replace pneumatic controls with DDC (250KSF)

Qty: 242,293.00

Unit of Measure: S.F.

Estimate: \$4,451,380.69

Assessor Name: System

Date Created: 09/22/2015

Notes: Replace the pneumatic controls for the HVAC systems with modern DDC modules, valves and actuators to improve reliability and energy efficiency. Provide a new building automation system (BAS) with communication interface to the preferred system in use throughout the District.

Equipment Inventory

The following table represents the inventory details of the inventory found in the building, which fall under the following subsystems:

Subsystem	Inventory	Qty	UoM	Location	Manufacturer	Model Number	Serial Number	Barcode	Life	Install Date	Next Renewal	Raw Cost	Inventory Cost
Systems	Boiler, gas/oil combination, cast iron, steam, gross output, 5810 MBH, includes burners, controls and insulated jacket, packaged	2.00	Ea.	Boiler Room	Weil McLain	2194	B259087-97		35	1997	2032	\$136,832.50	\$301,031.50
Systems	Boiler, gas/oil combination, cast iron, steam, gross output, 5810 MBH, includes burners, controls and insulated jacket, packaged	2.00	Ea.	Boiler Room	Weil McLain	2194	B259086-97		35	1997	2032	\$136,832.50	\$301,031.50
,	Pump, circulating, cast iron, base mounted, coupling guard, bronze impeller, flanged joints, 10 H.P., to 600 GPM, 5" size	2.00	Ea.	Boiler Room	Chicago Pump				25	1995	2020	\$19,608.00	\$43,137.60
,	Pump, circulating, cast iron, base mounted, coupling guard, bronze impeller, flanged joints, 10 H.P., to 600 GPM, 5" size	2.00	Ea.	Boiler Room	Chicago Pump				25	1995	2020	\$19,608.00	\$43,137.60
	Pump, circulating, cast iron, close coupled, end suction, bronze impeller, flanged joints, 10 H.P., to 350 GPM, 3" size	1.00	Ea.	Boiler Room	Chicago Pump				25	1958	1983	\$7,210.50	\$7,931.55
												Total:	\$696,269.75

Executive Summary

Building condition is evaluated based on the functional systems and elements of a building and organized according to the UNIFORMAT II Elemental Classification. The grouping of these systems and elements and applying a current replacement value to them develops a representative building cost model. Cost Models are developed for similar building types and functions. Systems and their elements are evaluated based on their current replacement values, life cycles, installation dates and next renewal dates. Systems and their elements that are within their useful lives are further evaluated to identify current deficient conditions that may have a significant impact on a system's or element's remaining service life, and to determine if they are beyond their predicted expected life. The system's or element's current replacement value is based on RS Means Commercial Cost Data.

Following are the cost model's system details for this facility. The Replacement Value is the amount needed to replace the property of the same present value. The Current Repair Amount, also known as Condition Needs, represents the budgeted contractor installed costs plus owner's soft costs for the repair, replacement or renewal for a component or system level deficiency. It excludes contributing costs for other components or systems that might also be associated with the corrective actions due to packaging the work. Facility Condition Index (FCI) FCI is an industry-standard measurement of facility condition calculated as the ratio of the costs to correct a facility's deficiencies to the facility's Current Replacement Value. It ranges from 0% (new) to 100% (very poor). Condition Index (CI) is calculated as the sum of a renewable system's Remaining Service Life (RSL) divided by the sum of a system's Replacement Value (both values exclude soft-cost to simplify calculation updates) expressed as a percentage ranging from 100% (new) to 0% (expired).

Function:

Gross Area (SF): 17,300

Year Built: 1958

Last Renovation:

Replacement Value: \$594,428

Repair Cost: \$519,622.81

Total FCI: 87.42 %

Total RSLI: 106.05 %

Description:

Attributes:

General Attributes:

Bldg ID: S201001 Site ID: S201001

Condition Summary

The Table below shows the CI and FCI for each major building system shown at the UNIFORMAT classification Level II. Note that Systems with lower FCIs require less investment than systems with higher FCIs.

UNIFORMAT Classification	RSLI %	FCI %	Current Repair Cost
G20 - Site Improvements	105.64 %	92.75 %	\$329,726.83
G40 - Site Electrical Utilities	106.67 %	79.48 %	\$189,895.98
Totals:	106.05 %	87.42 %	\$519,622.81

Condition Detail

This section of the report contains results of the Facility Condition Assessment. The building is separated into system components based on UNIFORMAT II classification. The columns in the System Listing table below represent the following:

- 1. System Code: A code that identifies the system.
- 2. System Description: A brief description of a system present in the building.
- 3. Unit Price \$: The unit price of the system.
- 4. UoM: The unit of measure for of the system.
- 5. Qty: The quantity for the system
- 6. Life: anticipated service life for the system based on Building Owners and Managers Association (BOMA) recommendations.
- 7. Year Installed: The date of system installation.
- 8. Calc Next Renewal Year: The date of system expiration based on the life, NR stands for non renewable.
- 9. Next Renewal Year: The suggested system expiration date by the assessor based on visual inspection.
- 10. CI: The Condition Index of the system.
- 11. FCI: The Facility Condition Index of the system.
- 12. RSL: Remaining Service Life.
- 13. eCR: eCOMET Condition Rating (not used).
- 14. Deficiency \$: The financial investment to repair/replace system.

System Listing

The System Listing table below lists each of the systems organized by their UNIFORMAT II classification. The assessment team was tasked with recording the most recent replacement year of each system, determining the remaining service life based on the theoretical life, and evaluating the condition to confirm the forecast next replacement year. The system listing is the basis for all data contained in the Building Assessment Report.

Additionally, a condition rating (eCR) based on the following guidelines is provided as observed at the time of the assessment.

- Excellent (E) No noticeable distress or damage. The entire system is free from observable defect.
- Very Good (VG) Overall no serviceability reduction for the entire system. No degradation of critical components and minor distress and defect noticeable for some but not non critical components within the system.
- Good (G) Slight or no serviceability reduction for the entire system. There may be noticeable defects for some non critical components and slight noticeable degradation of the critical components.
- Fair (F) Overall serviceability is degraded but adequate. There may be moderate deterioration for very few of the critical components and few of the non critical components may have severe degradation.
- Marginal (MA) Overall serviceability and reliability loss. Most if not all of the non critical components suffer from severe degradation and a few of the critical component may have severe degradation.
- Moderate (MO) Overall a significant serviceability loss. Most if not all the components have severe degradation with the reminder of the component showing visible distress.
- Very Poor (VP) Overall the system is barely functional. All of the components are severely degraded.
- Non-Functional (NF) Overall the system does not function with all the components having no serviceability and suffer from severe degradation.

System						Year		Next Renewal						Replacement
Code	System Description	Unit Price \$	UoM	Qty	Life	Installed	Year	Year	RSLI%	FCI%	RSL	eCR	Deficiency \$	Value \$
G2010	Roadways	\$11.52	S.F.		30				0.00 %	0.00 %				\$0
G2020	Parking Lots	\$8.50	S.F.		30				0.00 %	0.00 %				\$0
G2030	Pedestrian Paving	\$16.19	S.F.	17,300	40	1971	2011	2057	105.00 %	25.68 %	42		\$71,914.25	\$280,087
G2040	Site Development	\$4.36	S.F.	17,300	25	1971	1996	2042	108.00 %	341.80 %	27		\$257,812.58	\$75,428
G2050	Landscaping & Irrigation	\$4.36	S.F.		15				0.00 %	0.00 %				\$0
G4020	Site Lighting	\$10.69	S.F.	17,300	30	1958	1988	2047	106.67 %	75.69 %	32		\$139,977.35	\$184,937
G4030	Site Communications & Security	\$3.12	S.F.	17,300	30	1958	1988	2047	106.67 %	92.48 %	32		\$49,918.63	\$53,976
								Total	106.05 %	87.42 %			\$519,622.81	\$594,428

System Notes

The facility description in the site executive summary contains an overview of each system. The notes listed below provide additional information on select systems found within the facility.

No data found for this asset

Renewal Schedule

eCOMET forecasts future Capital Renewal funding needed to address expiring systems based on the Next Renewal year found in the Cost Models. A 3% annual inflation factor is applied to the costs for systems expiring in future years. The table below reflects recommended Capital Renewal funding needs over the next 10 years. Note: Cells with a zero value indicate systems for which renewal is not scheduled in that year.


Inflation Rate: 3%

System	Current Deficiencies	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	Total
Total:	\$519,623	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$519,623
G - Building Sitework	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
G20 - Site Improvements	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
G2010 - Roadways	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
G2020 - Parking Lots	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
G2030 - Pedestrian Paving	\$71,914	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$71,914
G2040 - Site Development	\$257,813	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$257,813
G2050 - Landscaping & Irrigation	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
G40 - Site Electrical Utilities	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
G4020 - Site Lighting	\$139,977	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$139,977
G4030 - Site Communications & Security	\$49,919	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$49,919

^{*} Indicates non-renewable system

Forecasted Sustainment Requirement


The following chart shows the current building deficiencies and forecasting sustainment requirements over the next ten years.



10 Year FCI Forecast by Investment Scenario

The chart below illustrates the effect of various investment levels on the building FCI for the next 10 years. The levels of investment shown below include:


- Current FCI: a variable investment amount based on renewing expired systems to maintain the current FCI for the building
- 2% Investment: an annual investment of 2% of the replacement value of the building, escalated for inflation
- 4% Investment: an annual investment of 4% of the replacement value of the building, escalated for inflation



	Investment Amount	2% Investm	ent	4% Investment			
Year	Current FCI - 87.42%	Amount	FCI	Amount	FCI		
2016	\$0	\$12,245.00	85.42 %	\$24,490.00	83.42 %		
2017	\$693,693	\$12,613.00	193.42 %	\$25,225.00	189.42 %		
2018	\$0	\$12,991.00	191.42 %	\$25,982.00	185.42 %		
2019	\$0	\$13,381.00	189.42 %	\$26,761.00	181.42 %		
2020	\$0	\$13,782.00	187.42 %	\$27,564.00	177.42 %		
2021	\$0	\$14,196.00	185.42 %	\$28,391.00	173.42 %		
2022	\$0	\$14,621.00	183.42 %	\$29,243.00	169.42 %		
2023	\$0	\$15,060.00	181.42 %	\$30,120.00	165.42 %		
2024	\$0	\$15,512.00	179.42 %	\$31,024.00	161.42 %		
2025	\$0	\$15,977.00	177.42 %	\$31,954.00	157.42 %		
Total:	\$693,693	\$140,378.00		\$280,754.00			

Deficiency Summary by System


Current deficiencies included assemblies that have reached or exceeded their design life or components of the assemblies that are in need of repair. Assemblies that have reached their design life are identified as current deficiencies and assigned the distress 'Beyond Useful Life'. The following chart lists all current deficiencies associated with this facility.



Budget Estimate Total: \$519,622.81

Deficiency Summary by Priority

The following chart shows the total repair costs broken down by priority. Assessors assigned deficiencies within eCOMET to one of the following priority categories:



Budget Estimate Total: \$519,622.81


Deficiency By Priority Investment Table

The table below shows the current investment cost grouped by deficiency priority and building system.

System				3 - Response			
Code	System Description	Time (< 2 yr)	Time (2-3 yrs)	Time (3-4 yrs)	Time (4-5 yrs)	Time (> 5 yrs)	Total
G2030	Pedestrian Paving	\$0.00	\$0.00	\$0.00	\$71,914.25	\$0.00	\$71,914.25
G2040	Site Development	\$0.00	\$0.00	\$257,812.58	\$0.00	\$0.00	\$257,812.58
G4020	Site Lighting	\$0.00	\$0.00	\$139,977.35	\$0.00	\$0.00	\$139,977.35
G4030	Site Communications & Security	\$0.00	\$0.00	\$0.00	\$49,918.63	\$0.00	\$49,918.63
	Total:	\$0.00	\$0.00	\$397,789.93	\$121,832.88	\$0.00	\$519,622.81

Deficiency Summary by Category

The following chart shows the total repair costs broken down by deficiency categories. Assessors assigned deficiencies to one of the following categories:



Deficiency Details by Priority

The deficiency detail notes listed below provide additional information on identified deficiencies found within the facility.

Priority 3 - Response Time (3-4 yrs):

System: G2040 - Site Development



Location: Grounds/ site

Distress: Damaged

Category: 3 - Operations / Maint.

Priority: 3 - Response Time (3-4 yrs)

Correction: Repair exterior brick retaining wall - per LF of

wall - up to 4' tall

Qty: 500.00

Unit of Measure: L.F.

Estimate: \$257,812.58

Assessor Name: Craig Anding

Date Created: 10/15/2015

Notes: Repair retaining walls, re-set stone cladding and replace stone coping

System: G4020 - Site Lighting



Location: Grounds

Distress: Building / MEP Codes

Category: 2 - Code Compliance

Priority: 3 - Response Time (3-4 yrs)

Correction: Add Site Lighting - pole mounted - select the

proper light and pole

Qty: 1.00

Unit of Measure: Ea.

Estimate: \$139,977.35

Assessor Name: Craig Anding

Date Created: 10/15/2015

Notes: Install additional outdoor lighting

Priority 4 - Response Time (4-5 yrs):

System: G2030 - Pedestrian Paving



Location: Grounds/ site

Distress: Beyond Service Life

Category: 3 - Operations / Maint.

Priority: 4 - Response Time (4-5 yrs)

Correction: Remove and replace concrete sidewalk or

concrete paving - 4" concrete thickness

Qty: 5,000.00

Unit of Measure: S.F.

Estimate: \$71,914.25

Assessor Name: Craig Anding

Date Created: 10/15/2015

Notes: Resurface entry plaza paving

System: G4030 - Site Communications & Security



Notes: Install additional Speakers outdoor for paging.

Location: grounds

Distress: Security Issue

Category: 1 - Health & Safety

Priority: 4 - Response Time (4-5 yrs)

Correction: Add Site Paging System

Qty: 0.00

Unit of Measure: Ea.

Estimate: \$49,918.63

Assessor Name: Craig Anding

Date Created: 10/15/2015

Equipment Inventory

The following table represents the inventory details of the inventory found in the building, which fall under the following subsystems:

No data found for this asset

Glossary

ABMA American Boiler Manufacturers Association http://www.abma.com/

ACEEE American Council for an Energy-Efficient Economy

ACGIH American Council of Governmental and Industrial Hygienists

AEE Association of Energy Engineers

AFD Adjustable Frequency Drive

AFTC After Tax Cash Flow

AGA American Gas Association

AHU Air Handling Unit

Amp Ampere

ANSI American National Standards Institute

ARI Air Conditioning and Refrigeration Institute

ASD Adjustable Speed Drive

ASHRAE American Society of Heating Refrigerating and Air-Conditioning Engineers Inc.

ASME American Society of Mechanical Engineers

Assessment Visual survey of a facility to determine its condition. It involves looking at the age of systems

reviewing information from local sources and visual evidence of potential problems to assign a condition rating. It does not include destructive testing of materials or testing of systems or

equipment for functionality.

ATS After Tax Savings

AW Annual worth

BACNET Building Automation Control Network

BAS Building Automation System

BCR Benefit Cost Ratio

BEP Business Energy Professional (AEE)

BF Ballast Factor

BHP Boiler Horsepower (boilers)

BHP Brake Horsepower (motors)

BLCC Building Life Cycle Cost analysis program (FEMP)

BOCA Building Officials and Code Administrators

BTCF Before Tax Cash Flow

BTS Before Tax Savings

Btu British thermal unit

Building Addition An area space or component of a building added to a building after the original building's year

built date.

CAA Clean Air Act

CAAA-90 Clean Air Act Amendments of 1990

CABO Council of American Building Officials

CAC Conventional Air Conditioning

CADDET Center for the Analysis and Dissemination of Demonstrated Energy Technologies

Calculated Next Renewal The year a system or element would be expected to expire based solely on the date it was

installed and the expected useful lifetime for that kind of system.

Capital Renewal Capital renewal is condition work (excluding suitability and energy audit work) that includes the

replacement of building systems or elements (as they become obsolete or beyond their useful life) not normally included in an annual operating budget. Calculated next renewal The year a system or element would be expected to expire based solely on the date it was installed and the expected useful lifetime for that kind of system. Next renewal The assessor adjusted expected useful life

of a system or element based on on-site inspection.

CDD Cooling Degree Days

CDGP Certified Distributed Generation Professional

CEC California Energy Commission

CEM Certified Energy Manager

CEP Certified Energy Procurement Professional

CFC Chlorofluorocarbon

CFD Cash Flow Diagram

CFL Compact Fluorescent Light

CFM cfm Cubic Feet per Minute

CHP Combined Heat and Power (a.k.a. cogeneration)

CHW Chilled Water

Condition Condition refers to the state of physical fitness or readiness of a facility system or system element

for its intended use.

COP Coefficient of Performance

Cp Heat Capacity of Material

CPUC California Public Utility Commission

CRI Color Rendering Index

CRT Cathode Ray Tube VDT HMI

CTC Competitive Transition Charge

Cu Coefficient of Utilization

Current Replacement

Value (CRV)

CRV represents the hypothetical total cost of rebuilding or replacing an existing facility in current dollars to its optimal condition (excluding auxiliary facilities) under current codes and construction

standards.

Cv Value Coefficient

CWS Chilled Water System

D d Distance (usually feet)

DB Dry Bulb

DCV Demand Control Ventilation

DD Degree Day

DDB Double Declining Balance

DDC Direct Digital Controls

Deferred maintenance Deferred maintenance is condition work (excluding suitability and energy audit needs) deferred on

a planned or unplanned basis to a future budget cycle or postponed until funds are available.

Deficiency A deficiency is a repair item that is damaged missing inadequate or insufficient for an intended

purpose.

Delta Difference

Delta P Pressure Difference

Delta T Temperature Difference

DG Distributed Generation

DOE Department of Energy

DP Dew Point

DR Demand Response

DX Direct Expansion Air Conditioner

EA Energy Audit

EBITDA Earnings before Interest Taxes Depreciation and Amortization

ECI Energy Cost Index

ECM Energy Conservation Measure

ECO Energy Conservation Opportunity

ECPA Energy Conservation and Production Act

ECR Energy Conservation Recommendation

ECS Energy Control System

EER Energy Efficiency Ratio

EERE Energy Efficiency and Renewable Energy division of US DOE

EIA Energy Information Agency

EIS Energy Information System

EMCS Energy Management Computer System

EMO Energy Management Opportunity

EMP Energy Management Project

EMR Energy Management Recommendation

EMS Energy Management System

Energy Utilization Index

(EUI)

EUI is the measure of total energy consumed in the cooling or heating of a building in a period

expressed as British thermal unit (BTU) per (cooled or heated) gross square foot.

EO Executive Order

EPA Environmental Protection Agency

EPACT Energy Policy Act of 1992

EPCA Energy Production and Conservation Act of 1975

EPRI Electric Power Research Institute

EREN Efficiency and Renewable Energy (Division of USDOE)

ERV Energy Recovery Ventilator

ESCO Energy Service Company

ESPC Energy Savings Performance Contract

EUI Energy Use Index

EWG Exempt Wholesale Generators

Extended Facility
Condition Index (EFCI)

EFCI is calculated as the condition needs for the current year plus facility system renewal needs

going out to a set time in the future divided by Current Replacement Value.

f Frequency

Fahrenheit

Facility A facility refers to site(s) building(s) or building addition(s) or combinations thereof that provide a

particular service.

Facility Condition Assessment (FCA) FCA is a process for evaluating the condition of buildings and facilities for programming and

budgetary purposes through an on site inspection and evaluation process.

Facility Condition Index

(FCI)

FCI is an industry-standard measurement of a facility's condition that is the ratio of the cost to correct a facility's deficiencies to the Current Replacement Value of the facilities. The higher the

FCI the poorer the condition of a facility. After an FCI is established for all buildings within a portfolio a building's condition can be ranked relative to other buildings. The FCI may also represent the condition of a portfolio based on the cumulative FCIs of the portfolio's facilities.

FC Footcandle

FCA Fuel Cost Adjustment

FEMIA Federal Energy Management Improvement Act of 1988

FEMP Federal Energy Management Program

FERC Federal Energy Regulatory Commission

FESR Fuel Energy Savings Ratio

FLA Full Load Amps

FLF Facility Load Factor (usually monthly)

FLRPM Full Load Revolutions per Minute

FMS Facility Management System

FPM fpm Feet per Minute (velocity)

FSEC Florida Solar Energy Center

Ft Foot

GPM gpm Gallons per Minute

GRI Gas Research Institute

Gross Square Feet (GSF) The size of the enclosed floor space of a building in square feet measured to the outside face of

the enclosing wall.

GUI Graphical User Interface

H h Enthalpy Btu/lb

HCFC Hydrochlorofluorocarbons

HDD Heating Degree days

HFC Hydrofluorocarbons

HHV Higher Heating Value

HID High Intensity Discharge (lamp)

HMI Human Machine Interface

HMMI Human Man Machine Interface

HO High Output (lamp)

HP Hp hp Horsepower

HPS High Pressure Sodium (lamp)

HR Humidity Ratio

Hr hr Hour

HRU Heat Recovery Unit

HVAC Heating Ventilation and Air-Conditioning

Hz Hertz

I Intensity (lumen output of lamp)

I i Interest rate or Discount rate

IAQ Indoor Air Quality

ICA International Cogeneration Alliance

ICBO International Conference of Buildings Officials

ICC International Code Council

ICP Institutional Conservation Program

IECC International Energy Conservation Code

IEEE Institute of Electrical and Electronic Engineers

IESNA Illuminating Engineering Society of North America

Install year The year a building or system was built or the most recent major renovation date (where a

minimum of 70 of the system?s Current Replacement Value (CRV) was replaced).

IRP Integrated Resource Planning

IRR Internal Rate of Return

ISO Independent System Operator

ITA Independent Tariff Administrator

k Kilo multiple of thousands in SI system

K Kelvins (color temperature of lamp)

K k Thermal Conductivity of Material

KVA Kilovolt Ampere

KVAR Kilovolt Ampere Reactive

kW kiloWatt

kWh kiloWatt hour

Length (usually feet)

LCC Life Cycle Costing

LDC Local Distribution Company

LEED Leadership in Energy and Environmental Design

LEED EB LEED for Existing Buildings

LEED NC LEED for new construction

LF Load Factor

LHV Lower Heating Value

Life cycle The period of time that a building or site system or element can be expected to adequately serve

its intended function.

LPS Low Pressure Sodium (lamp)

Lumen Output of a Lamp or Fixture

M Mega multiple of millions in SI system

M&V Measurement and Verification

MACRS Modified Accelerated Cost Recovery System

MARR Minimum Attractive Rate of Return

Mbtu Thousand Btu

MCF Thousand Cubic Feet (usually of gas)

MEC Model Energy Code

Mm Multiple of Thousands in I/P System

MMBtu Million Btu

MMCS Maintenance Management Computer System

MMI Man Machine Interface

MMS Maintenance Management System

MSE 2000 Management System for Energy 2000 (ANSI Georgia Tech Univ)

MW MegaWatt

MWH MWh MegaWatt hour

NAAQS National Ambient Air Quality Standards

NAESCO National Association of Energy Service Companies

NAIMA North American Insulation Manufacturers Association

NEA National Energy Act of 1978

NECPA National Energy Conservation Policy Act

NEMA National Electrical Manufacturer's Association

NERC North American Electric Reliability Council

Next Renewal The Next Renewal date is an override of the 'Calculated Next Renewal' date and is based upon the

assessor?s visual inspection.

NFPA National Fire Protection Association

NGPA National Gas Policy Act of 1978

NLRPM No Load Revolutions per Minute (speed)

Nn Equipment or Project lifetime in economic analysis

NOPR Notice of Proposed Rule Making from FERC

NOx Nitrogen Oxide Compounds

NPV Net present value in economic analysis

NREL National Renewable Energy Laboratory

NUG Non-Utility Generator

O&M Operation and Maintenance

OA Outside Air

ODP Ozone Depletion Potential

OPAC Off-Peak Air Conditioning

P Present value in economic analysis

PBR Performance Based Rates

PEA Preliminary Energy Audit

PF Power Factor

PID Proportional plus integral plus derivative (control system)

PM Portfolio Manager in Energy Star rating system

PM Preventive Maintenance

PoolCo Power Pool Company or Organization

POU Point of Use

PQ Power Quality

PSC Public Service Commission

PSIA psia Pounds per square inch absolute (pressure)

PSIG psig Pounds per square inch gauge (pressure)

PUC Public Utility Commission

PUHCA Public Utilities Holding Company Act of 1935

PURPA Public Utilities Regulatory Policies of 1978

PV Photovotaic system

PV Present Value

PW Present Worth

PX Power Exchange

q Rate of heat flow in Btu per hour

Q Heat load due to conduction using degree days

QF Qualifying Facility

R Electrical resistance

R Thermal Resistance

RC Remote controller

RCR Room Cavity Ratio

RCRA Resource Conservation and Recovery Act

Remaining Service Life

(RSL)

RSL is the number of years service remaining for a system or equipment item. It is automatically calculated based on the difference between the current year and the 'Calculated Next Renewal'

date or the 'Next Renewal' date whichever one is the later date.

Remaining Service Life

Index (RSLI)

RSLI is defined as a percentage ratio of the remaining service life of a system. It usually ranges

from 0 to 100

REMR Repair Evaluation Maintenance Rehabilitation (REMR) is a scale used to objectively rank systems

based on their condition

Renewal Schedule A timeline that provides the items that need repair the year in which the repair is needed and the

estimated price of the renewal.

RH Relative Humidity

RLA Running Load Amps

RMS Root Mean Square

RO Reverse Osmosis

ROI Return on Investment

RPM Revolutions Per Minute

RTG Regional Transmission Group

RTO Regional Transmission Organization

RTP Real Time Pricing

SBCCI Southern Building Code Congress International

SC Scheduling Coordinator

SC Shading Coefficient

SCADA Supervisory Control and Data Acquisition Systems

SEER Seasonal Energy Efficiency Ratio

SHR Sensible Heat Ratio

Site The grounds and utilities roadways landscaping fencing and other typical land improvements

needed to support the facility.

Soft Cost An expense item that is not considered direct construction cost. Soft cost includes architectural

engineering financing legal fees and other pre-and-post construction expenses.

SOx Sulfur Oxide Compounds

SP Static Pressure

SP SPB Simple Payback

SPP Simple Payback Period

SPP Small Power Producers

STR Stack Temperature Rise

SV Specific Volume

System System refers to building and related site work elements as described by ASTM Uniformat II

Classification for Building Elements (E1557-97) a format for classifying major facility elements common to most buildings. Elements usually perform a given function regardless of the design

specification construction method or materials used. See also Uniformat II.

T Temperature

T Tubular (lamps)

TAA Technical Assistance Audit

TCP/IP Transmission Control Protocol/Internet Protocol

TES Thermal Energy Storage

THD Total Harmonic Distortion

TOD Time of Day

TOU Time of Use

TQM Total Quality Management

TransCo Transmission Company

U Thermal Conductance

UDC Utility Distribution Company

UL Underwriters Laboratories

UNIFORMAT II The ASTM UNIFORMAT II Classification for Building Elements (E1557-97) a format for classifying

major facility components common to most buildings.

USGBC US Green Building Council

v Specific Volume

V Volts Voltage

V Volume

VAV Variable Air Volume

VDT Video Display Terminal

VFD Variable Frequency Drive

VHO Very High Output

VSD Variable Speed Drive

W Watts W Width

WB Wet bulb

WH Wh Watt Hours

Year built The year that a building or addition was originally built based on substantial completion or

occupancy.

Z Electrical Impedance

APPENDIX B COST ESTIMATE COVER SHEET

Project:		Estimated By:	
Contract Number: N/A	Construction Estimate	Date:	
School:		Drawing Status:	
Address:			
Coope of Work			
Scope of Work:			

Description	GC Contract	MC Contract	PC Contract	EC Contract	Total
Total Material				_	_
Total Equipment				_	_
Total Labor					
Total Material, Equipment & Labor	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
General Conditions: 10%	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
Sub-total	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
Estimate Contingency 10%	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
Sub-total	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
15% OH & Profit	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
Subtotal	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
2% bond:	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
Subtotal	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
3% Escalation	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
Subtotal Construction Cost	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
environmental estimate from OEMS	φυ.υυ	\$0.00	φυ.υυ	\$0.00	φυ.υυ
\$ XXXXX plus 15% OH&P	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00
Total Construction Cost	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00